Jammu & Kashmir

OFFICE OF THE EXECUTIVE ENGINEER PHE DIVISION SOPORE

M/s Classic Construction Co. Prop: Shabir Mustafa Rafiqui,

R/o: 28-A Polo View Srinagar Kmr.

9324-31 Dated: 16-61-2023

Time of Compl.:150days

Subject: -

Construction/Testing/Commissioning of over head Tank's (OHT) along with allied works in different divisions/ Districts of Kashmir Province under Jal Javeen Mission.

Ref:

1. Your on-line tender received in response to the E-NIT No: 129 of under endorsement 21-02-2022 issued 2021-22 dated: CE/PHE/DB/41981-42033 dated: 21-02-2022.

2. Chief Engineer Kashmir Jal Shakti PHE Department Srinagar's

letter No: CE/PHE/JJM/2617-59 dated: 5-5-2022.

3. Superintending Hyd. Circle Sopore's authorization issued order No:

SE/Hyd./DB/3905-17 dated: 16-7-2022.

For and on behalf of Lt. Governor of Jammu and Kashmir Union Territory, contract for the work namely "Construction/Testing/Commissioning of 0.55 lac gallons capacity RCC OHT Shell type with Staging Height of 20 Mts including construction of sluice chamber Bunpora site at Naidkhai for W.S.Scheme Sadatpora Naidkhai under JJM'' is hereby allotted to you in accordance with the terms and conditions as laid down in the bid document read with any amendment if any for an amount of Rs.9455776.0/= (Rs.Ninety four lacs fifty five thousand seven hundred and seventy six only) as per the following item rates along with your quoted overall tender appreciation of 4% (Four percent)

appre	eciation of 4% (Four percent)				
<u>A</u>	Rates: Particulars of Items	Unit	Quantity	Allotted	Amount in
S.	Paiticulars of Rome			Rate	Rs.
No 1.	Earth work in bulk excavation by mechanical means (hydraulic excavator) over areas (exceeding 30 cm in depth, 1.5 m in width as well as 10 m2 on plan) including disposal of excavated earth lead upto 50 meters and lift upto 1.5 m, as directed by Engineer-in-Charge. All kinds of soil & sluice chamber 3.6x3.6x1m Earth work in bulk excavation by manual means over areas (exceeding 30 cm in depth, 1.5 m in width as well as 10 m2 on plan) including disposal of excavated earth lead upto 50 meters	Cun	645.00	188.75	121745.00
3.	and lift upto 1.5 m, as directed by Finghton 1.5 Charge. All kinds of soils	Cum	161.00	539.35	86835.00
۵.	thereof in excavation/banking excavated or stacked material; All kinds of soil	Cum	371.00	81.65	30291.00
			RA LE	\$	Exen.

Head Draftsman

Technical Officer

Page No: 02

	Page No: 02	anaci	tv at Naidl	rhai	
j.	Page No: U2 Construction of 0.55 lac Gallons C	Unit	Quantity	Allotted	Amount in
	Particulars of Items	J1111	-	Rate	Rs.
S.					
No	Carriage of excavated soil to be dumped at Gulabwari				
4.	Carriage of excavated soil to be dufing carriage of the side average lead3.0kms including carriage of the		. 1	1	000411.00
	side average lead3.0kms including carriage dumped soil back for filling after completion of the	Cum/	1612.09	187.60	302411.00
		Udaniy	/	1	/
5.		1			
5.	river scepage, broken water mains or drains and	KL	371.00	155.55	57710.00
	. 111	KD		11	71
	to beging in trenches including structure,	/(′
6.	1				
	1 / Managements to be taken of the fact			,	<i>a</i>
	I I I I I Don'th overeding L.J III but not	C	54.00	247.75	13378.00
	1: 2	Sqm	34.00	1	7
-	Providing and laying hand packed stolle solling	1	1		,
7.	(Ouerry) including ramining and discours		,		
	including all leads lifts and all carriages	0	89.70	1320.00	118404.00
		Cum	89.70	1020.007	
-		/	,		
8.					
				. 1	
1	level with: 1.4.8 [1 cement : 4 coarse sand : 5 grand]	Cum	27.62	4861.84	134284.00
1	1 and the state of	/	1		
Ç	Centering and shuttering including structing,	/	,		
	to and removal of form for the			,	
	Foundations, footings, bases of columns etc. for	Sqm	30.46	262.30	7990.00
	mass concrete.	Sqiii	1 33.13		1
	10. Centering and shuttering including strutting,				
	propping etc. and removal of form for: Walls (any				
	thickness) including attached pilasters,	Sqm	1052.00	√ 573.85 /	603690.20
	buttresses, plinth and string courses etc	Sqii	1002.00	1 0,0:00	1
	11. Centering and shuttering including strutting, propping etc. and removal of form for: Lintel, beams,	1			
	plinth beams, girders, bressumers and cantilevers.	Sqn	n / 95.24	<i>§</i> 502.85	47891.00
-				1	
	12. Centering and shuttering including strutting, propping etc. and removal of form for:			\	
1	Suspended floors, roofs, landings, balconies and	1	,		
	access platforms.	Sqn	n/ 12.10	635.60	7691.00
	13. Centering and shuttering including strutting,		1	()	
	propping etc. and removal of form for: Arches,			.]	
	domes, vaults upto 6 m span	Sqr	n/ 115.50	2086.80	/ 241025.00/
	14. Extra for arches, domes, vaults exceeding 6 m	1	1		7
	span	Sqr	n/115.50	1008.45	116476.00
	15. Extra for Spiral stair including landings	Sq			35682.00
	16. Extra for shuttering in circular work (20% of	f			
	respective centering and Shuttering items).				
	17. Foundations, footings, bases of columns etc. for	r	/		A .
	mass concrete	Sq	m/ 26.40	52.46	1384.00
	18. Walls (any thickness) including attached		1		1000
	pilasters, buttresses, plinth and string course	e			1
	etc participation of the straining courses	Sq Sq	m / 1017.0	0 114.77	116721.00
	19. Lintel, beams, plinth beams, girders, bressumer	s		-	
	and cantilevers.		m 95.34	100.57	9589.00
		1	30.04	1 100.37	3003.00
			1	*	L

Page No: 03

Providing and laying in position specified grade of reinforced cement concrete including curing but excluding the cost of centering, shuttering, finishing and reinforcement. All works upto plinth level 1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20 mm nominal size) 1. Reinforced cement concrete work in walls (any thickness) including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts upto floor five level including curing but excluding cost of centering shuttering, finishing and reinforcement. 1:1½:3 (1 cement: 1½ coarse sand: 3 graded stone aggregate 20 mm nominal size) 22. Providing and laying in position ready mixed M-25 grade concrete for reinforced cement concrete work, using flyash and cement content as per approved design mix, manufactured in fully automatic batching plant and transported to site of work in transit mixer for all leads, having continuous agitated mixer, manufactured as per mix design of specified grade for reinforced cement concrete work including pumping of R.M.C. from transit mixer to site of laying, excluding the cost of centering, shuttering finishing and reinforcement including cost of admixtures in recommended proportions as per IS: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge. All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note: Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M.30 grade concrete instead of M-25 grade BMC/RMC. (Note: Cement content considered in M-30 is@ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V-level for each four floors or part the		Construction of 0.55 lac Gallons Construction	apacit	y at Naidkl	ıai	
Providing and laying in position specified grade of reinforced cement concrete including curing but excluding the cost of centering, shuttering, finishing and reinforcement. All works upto plinth level 1:1½:3 (1 cement: 1½ coarse sand: 3 graded stone aggregate 20 mm nominal size) 1. Reinforced cement concrete work in walls (any thickness) including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts upto floor five level including curing but excluding cost of centering shuttering, finishing and reinforcement. 1:1½:3 (1 cement: 1½ coarse sand: 3 graded stone aggregate 20 mm nominal size) 22. Providing and laying in position ready mixed M-25 grade concrete for reinforced cement concrete work, using flyash and cement content as per approved design mix, manufactured in fully automatic batching plant and transported to site of work in transit mixer for all leads, having continuous agitated mixer, manufactured as per mix design of specified grade for reinforced cement concrete work including pumping of R.M.C. from transit mixer to site of laying, excluding the cost of centering, shuttering finishing and reinforcement including cost of admixtures in recommended proportions as per 18: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge. All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note: Excess/less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note: Cement content considered in M-30 is 66 304 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C., work above floor V level for each four floors or part thereof.	T	Particulars of Items	Unit	Quantity	Allotted	Amount in
Providing and laying in position specified grade of reinforced cement concrete including curring but excluding the cost of centering, shuttering, finishing and reinforcement. All works upto plinth level 1:1½:3 (1 cement: 1½ coarse sand: 3 graded stone aggregate 20 mm nominal size) Reinforced cement concrete work in walls (any thickness) including attached pilasters, buttresses, plinth and string courses, fillets, columns, pilars, piers, abutments, posts and struts upto floor five level including curing but excluding cost of centering shuttering, finishing and reinforcement. 11½:3 (1 cement: 1½ coarse sand: 3 graded stone aggregate 20 mm nominal size) Providing and laying in position ready mixed M-25 grade concrete for reinforced cement concrete work, using flyash and cement content as per approved design mix, manufactured in fully automatic batching plant and transported to site of work in transit mixer for all leads, having continuous agitated mixer, manufactured as per mix design of specified grade for reinforced cement concrete work including pumping of R.M.C. from transit mixer to site of laying, excluding the cost of centering, shuttering finishing and reinforcement including cost of admixtures in recommended proportions as per IS: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge. All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note: Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note: Cement content considered in M-30 is 63 404 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturers' specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 2		T divisions of the			Rate	Rs.
of reinforced cement concrete including curing but excluding the cost of centering, shuttering, finishing and reinforcement. All works upto plinth level 1:1½:3 (1 cement: 1½ coarse sand: 3 graded stone aggregate 20 mm nominal size) Reinforced cement concrete work in walls (any thickness) including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts upto floor five level including curing but excluding cost of centering shuttering, finishing and reinforcement. 1:1½:3 (1 cement: 1½ coarse sand: 3 graded stone aggregate 20 mm nominal size) Providing and laying in position ready mixed M-25 grade concrete for reinforced cement concrete work using flyash and cement content as per approved design mix, manufactured in fully automatic batching plant and transported to site of work in transit mixer for all leads, having continuous agitated mixer, manufactured as per mix design of specified grade for reinforced cement concrete work including pumping of R.M.C. from transit mixer to site of laying, excluding the cost of centering, shuttering finishing and reinforcement including cost of admixtures in recommended proportions as per IS: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer in - charge. All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note: Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note: Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straighteni	-	iding and laying in position specified grade				
but excluding the cost of centering, shuttering, finishing and reinforcement. All works upto plinth level 1:1½:3 (1 cement: 1½ coarse sand: 3 graded stone aggregate 20 mm nominal size) Reinforced cement concrete work in walls (any thickness) including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts upto floor five level including curing but excluding cost of centering shuttering, finishing and reinforcement. 1:1½:3 (1 cement: 1½ coarse sand: 3 graded stone aggregate 20 mm nominal size) 2. Providing and laying in position ready mixed M-25 grade concrete for reinforced cement concrete work, using flyash and cement content as per approved design mix, manufactured in fully automatic batching plant and transported to site of work in transit mixer for all leads, having continuous agitated mixer, manufactured as per mix design of specified grade for reinforced cement concrete work including pumping of R.M.C. from transit mixer to site of laying, excluding the cost of centering, shuttering finishing and reinforcement including cost of admixtures in recommended proportions as per 18: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge. All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting plending hinding and placing	Prov	sinforced cement concrete including curing				
finishing and reinforcement. All works upto plinth level 1:1½:3 (1 cement: 1½ coarse sand: 3 graded stone aggregate 20 mm nominal size) Reinforced cement concrete work in walls (any thickness) including attached pilasters, buttresses, plinth and string courses, fillets, columns, pilars, piers, abutments, posts and struts upto floor five level including curring but excluding cost of centering shuttering, finishing and reinforcement. 1:1½:3 (1) cement: 1½ coarse sand: 3 graded stone aggregate 20 mm nominal size) 2. Providing and laying in position ready mixed M-25 grade concrete for reinforced cement content as per approved design mix, manufactured in fully automatic batching plant and transported to site of work in transit mixer for all leads, having continuous agitated mixer, manufactured as per mix design of specified grade for reinforced cement concrete work including pumping of R.M.C. from transit mixer to site of laying, excluding the cost of centering, shuttering finishing and reinforcement including cost of admixtures in recommended proportions as per IS: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer: in - charge. All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note: Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting , bending , binding and placing in position complete-TMT bars of Grade	oi re	emoreta cement concrete mercang shuttering.				
plinth level 1:1½:3 (1 cement: 1½ coarses sand: 3 graded stone aggregate 20 mm nominal size) Reinforced cement concrete work in walls (any thickness) including attached pilasters, buttresses, plinth and string courses, fillets, columns, pilars, piers, abutments, posts and struts upto floor five level including curing but excluding cost of centering shuttering, finishing and reinforcement. 1:1½:3 (1 cement: 1½ coarse sand: 3 graded stone aggregate 20 mm nominal size) 2. Providing and laying in position ready mixed M-25 grade concrete for reinforced cement concrete work, using flyash and cement content as per approved design mix, manufactured in fully automatic batching plant and transported to site of work in transit mixer for all leads, having continuous agitated mixer, manufactured as per mix design of specified grade for reinforced cement concrete work including pumping of R.M.C. from transit mixer to site of laying, excluding the cost of centering, shuttering finishing and reinforcement including cost of admixtures in recommended proportions as per IS: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer in - charge. All works above plinth level upto floor V-level. 23. Extra for providing m.30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content used is payable/ recoverable separately. 5,35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C/B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting , bending , binding and placing in position complete-TMT bars of Grade	but	shing and reinforcement All works upto				
Reinforced cement concrete work in walls (any thickness) including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts upto floor five level including curing but excluding cost of centering shuttering, finishing and reinforcement. 1:1½:3 (1 cement: 1½ coarse sand: 3 graded stone aggregate 20 mm nominal size) 22. Providing and laying in position ready mixed M-25 grade concrete for reinforced cement concrete work, using flyash and cement content as per approved design mix, manufactured in fully automatic batching plant and transported to site of work in transit mixer for all leads, having continuous agitated mixer, manufactured as per mix design of specified grade for reinforced cement concrete work including pumping of R.M.C. from transit mixer to site of laying, excluding the cost of centering, shuttering finishing and reinforced erment including cost of admixtures in recommended proportions as per IS: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge. All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C., work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting , bending , binding and placing in position complete-TMT bars of Grade	linis	th level 1:116:3 (1 cement : 1½ coarse sand :		. 1	2	
Reinforced cement concrete work in walls (any thickness) including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts upto floor five level including curing but excluding cost of centering shuttering, finishing and reinforcement. 1:1½:3 (1 cement: 1½ coarse sand: 3 graded stone aggregate 20 mm nominal size) 20. Providing and laying in position ready mixed M-25 grade concrete for reinforced cement concrete work, using flyash and cement content as per approved design mix, manufactured in fully automatic batching plant and transported to site of work in transit mixer for all leads, having continuous agitated mixer, manufactured as per mix design of specified grade for reinforced cement concrete work including pumping of R.M.C. from transit mixer to site of laying, excluding the cost of centering, shuttering finishing and reinforcement including cost of admixtures in recommended proportions as per IS: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge. All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including and placing in position complete-TMT bars of Grade	piin	and stone aggregate 20 mm nominal size)	Cum 🛭	140.73	7800.76	1097800.00
thickness) including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abuttments, posts and struts upto floor five level including curing but excluding cost of centering shuttering, finishing and reinforcement. 1:1½:3 (1 cement: 1½ coarse sand: 3 graded stone aggregate 20 mm nominal size) 20 mm nominal size) 22. Providing and laying in position ready mixed M-25 grade concrete for reinforced cement concrete work, using flyash and cement content as per approved design mix, manufactured in fully automatic batching plant and transported to site of work in transit mixer for all leads, having continuous agitated mixer, manufactured as per mix design of specified grade for reinforced cement concrete work including pumping of R.M.C. from transit mixer to site of laying, excluding the cost of centering, shuttering finishing and reinforcement including cost of admixtures in recommended proportions as per 1S: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge. All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note: Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum] 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including and placing in position complete-TMT bars of Grade		forced cement concrete work in walls (any				
plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts upto floor five level including curing but excluding cost of centering shuttering, finishing and reinforcement. 1:1½; 3 (1 cement: 1½; coarse sand: 3 graded stone aggregate 20 mm nominal size) 20 mm nominal size) 21. Providing and laying in position ready mixed M-25 grade concrete for reinforced cement concrete work, using flyash and cement content as per approved design mix, manufactured in fully automatic batching plant and transported to site of work in transit mixer for all leads, having continuous agitated mixer, manufactured as per mix design of specified grade for reinforced cement concrete work including pumping of R.M.C. from transit mixer to site of laying, excluding the cost of centering, shuttering finishing and reinforcement including cost of admixtures in recommended proportions as per IS: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting , bending , binding and placing in position complete-TMT bars of Grade	. Ken	demand including attached pilasters, buttresses,		,		
piers, abutments, posts and struts upto floor live level including curing but excluding cost of centering shuttering, finishing and reinforcement. 1:1½:3 (1 cement: 1½ coarse sand: 3 graded stone aggregate 20 mm nominal size) 20 mm nominal size) 21. Providing and laying in position ready mixed M-25 grade concrete for reinforced cement concrete work, using flyash and cement content as per approved design mix, manufactured in fully automatic batching plant and transported to site of work in transit mixer for all leads, having continuous agitated mixer, manufactured as per mix design of specified grade for reinforced cement concrete work including pumping of R.M.C. from transit mixer to site of laying, excluding the cost of centering, shuttering finishing and reinforcement including cost of admixtures in recommended proportions as per IS: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting , bending , binding and placing in position complete-TMT bars of Grade	thic	the and string courses fillets columns, pillars,				
level including curing but excluding cost of centering shuttering, finishing and reinforcement. 1:1½:3 (1 cement: 1½ coarse sand: 3 graded stone aggregate 20 mm nominal size) 20 mm nominal size) Providing and laying in position ready mixed M-25 grade concrete for reinforced cement concrete work, using flyash and cement content as per approved design mix, manufactured in fully automatic batching plant and transported to site of work in transit mixer for all leads, having continuous agitated mixer, manufactured as per mix design of specified grade for reinforced cement concrete work including pumping of R.M.C. from transit mixer to site of laying, excluding the cost of centering, shuttering finishing and reinforcement including cost of admixtures in recommended proportions as per IS: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge. All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting , bending , binding and placing in position complete-TMT bars of Grade	plin	and string courses, inneres, containing to				
shuttering, finishing and reinforcement. 1:11/2:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20 mm nominal size) 2. Providing and laying in position ready mixed M-25 grade concrete for reinforced cement concrete work, using flyash and cement content as per approved design mix, manufactured in fully automatic batching plant and transported to site of work in transit mixer for all leads, having continuous agitated mixer, manufactured as per mix design of specified grade for reinforced cement concrete work including pumping of R.M.C. from transit mixer to site of laying , excluding the cost of centering, shuttering finishing and reinforcement including cost of admixtures in recommended proportions as per IS : 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge. All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in closes by weight of cement concrete work in closes by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting , bending , binding and placing in position complete-TMT bars of Grade	pie	rs, abutments, posts and strate aptering	*			
cement: 1½ coarse sand: 3 graded stone aggregate 20 mm nominal size) 20 mm nominal size) Providing and laying in position ready mixed M-25 grade concrete for reinforced cement concrete work, using flyash and cement content as per approved design mix, manufactured in fully automatic batching plant and transported to site of work in transit mixer for all leads, having continuous agitated mixer, manufactured as per mix design of specified grade for reinforced cement concrete work including pumping of R.M.C. from transit mixer to site of laying, excluding the cost of centering, shuttering finishing and reinforcement including cost of admixtures in recommended proportions as per IS: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge. All works above plinth level upto floor V-level. Note: Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note: Cement content considered in M-30 is@ 340 kg/cum) Cum/ 41.59 Providing and mixing water proofing material in cement concrete work in doses by weight of cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. Cum/ 41.59 309.05 2262 Cum/ 41.59	leve	el including curing but excluding cost of the state of th				
20. mm nominal size) 22. Providing and laying in position ready mixed M-25 grade concrete for reinforced cement concrete work, using flyash and cement content as per approved design mix, manufactured in fully automatic batching plant and transported to site of work in transit mixer for all leads, having continuous agitated mixer, manufactured as per mix design of specified grade for reinforced cement concrete work including pumping of R.M.C. from transit mixer to site of laying, excluding the cost of centering, shuttering finishing and reinforcement including cost of admixtures in recommended proportions as per IS: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting , bending , binding and placing in position complete-TMT bars of Grade	sh	uttering, liftishing and reinforcements				
2. Providing and laying in position ready mixed M-25 grade concrete for reinforced cement concrete work, using flyash and cement content as per approved design mix, manufactured in fully automatic batching plant and transported to site of work in transit mixer for all leads, having continuous agitated mixer, manufactured as per mix design of specified grade for reinforced cement concrete work including pumping of R.M.C. from transit mixer to site of laying, excluding the cost of centering, shuttering finishing and reinforcement including cost of admixtures in recommended proportions as per IS: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge. All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting bending , binding and placing in position complete-TMT bars of Grade			Cum	97.00	9408.14	912589.00
grade concrete for reinforced cement content as per approved design mix, manufactured in fully automatic batching plant and transported to site of work in transit mixer for all leads, having continuous agitated mixer, manufactured as per mix design of specified grade for reinforced cement concrete work including pumping of R.M.C. from transit mixer to site of laying, excluding the cost of centering, shuttering finishing and reinforcement including cost of admixtures in recommended proportions as per IS: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge. All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting , bending , binding and placing in position complete-TMT bars of Grade	20	min nominal size)	1	1		/
using flyash and cement content as per approved design mix, manufactured in fully automatic batching plant and transported to site of work in transit mixer for all leads, having continuous agitated mixer, manufactured as per mix design of specified grade for reinforced cement concrete work including pumping of R.M.C. from transit mixer to site of laying, excluding the cost of centering, shuttering finishing and reinforcement including cost of admixtures in recommended proportions as per IS: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge. All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C. C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting , bending , binding and placing in position complete-TMT bars of Grade	2. Pr	oviding and laying in position roady mines in 20	, ,			
design mix, manufactured in fully automatic batching plant and transported to site of work in transit mixer for all leads, having continuous agitated mixer, manufactured as per mix design of specified grade for reinforced cement concrete work including pumping of R.M.C. from transit mixer to site of laying, excluding the cost of centering, shuttering finishing and reinforcement including cost of admixtures in recommended proportions as per IS: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting , bending , binding and placing in position complete-TMT bars of Grade	gr	ade concrete for remoted coment as per approved				
plant and transported to site of work in transit mixer for all leads, having continuous agitated mixer, manufactured as per mix design of specified grade for reinforced cement concrete work including pumping of R.M.C. from transit mixer to site of laying, excluding the cost of centering, shuttering finishing and reinforcement including cost of admixtures in recommended proportions as per IS: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting , bending , binding and placing in position complete-TMT bars of Grade	\ u:	sing flyash and cement content up per approximation and cement				
for all leads, having continuous agitated mixer, manufactured as per mix design of specified grade for reinforced cement concrete work including pumping of R.M.C. from transit mixer to site of laying, excluding the cost of centering, shuttering finishing and reinforcement including cost of admixtures in recommended proportions as per IS: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting , bending and placing in position complete-TMT bars of Grade	d	esign mix, manufactured in rang date many transit mixer				
manufactured as per mix design of specified grade for reinforced cement concrete work including pumping of R.M.C. from transit mixer to site of laying, excluding the cost of centering, shuttering finishing and reinforcement including cost of admixtures in recommended proportions as per IS: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting ,bending ,binding and placing in position complete-TMT bars of Grade	p	lant and transported to site of word and transported to site o				
reinforced cement concrete work including pumping of R.M.C. from transit mixer to site of laying, excluding the cost of centering, shuttering finishing and reinforcement including cost of admixtures in recommended proportions as per IS: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge. All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting ,bending ,binding and placing in position complete-TMT bars of Grade	10	or all leads, having continuous agreement of specified grade for				
R.M.C. from transit mixer to site of laying, excluding the cost of centering, shuttering finishing and reinforcement including cost of admixtures in recommended proportions as per IS: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting bending binding and placing in position complete-TMT bars of Grade	\ 1	rainforced cement concrete work including pumping of				
the cost of centering, shuttering finishing and reinforcement including cost of admixtures in recommended proportions as per IS: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting ,bending ,binding and placing in position complete-TMT bars of Grade		P.M.C. from transit mixer to site of laying, excluding				
reinforcement including cost of admixtures in recommended proportions as per IS: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting ,bending ,binding and placing in position complete-TMT bars of Grade	1	the cost of centering, shuttering finishing and			,	
recommended proportions as per IS: 9103 to accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting ,bending ,binding and placing in position complete-TMT bars of Grade	1	reinforcement including cost of admixtures in				
accelerate/ retard setting of concrete, improve workability without impairing strength and durability as per direction of the Engineer- in - charge All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting ,bending ,binding and placing in position complete-TMT bars of Grade	1	recommended proportions as per IS: 9103 to				
workability without impairing strength and durability as per direction of the Engineer- in - charge All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting ,bending ,binding and placing in position complete-TMT bars of Grade	1	accelerate/ retard setting of concrete, improve				
as per direction of the Engineer- in - charge All works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting ,bending ,binding and placing in position complete-TMT bars of Grade		workability without impairing strength and durability				
works above plinth level upto floor V-level. 23. Extra for providing richer mixes at all floor levels. Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting ,bending ,binding and placing in position complete-TMT bars of Grade	1	as per direction of the Engineer- in - charge All		}		205010.0
Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R,M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting ,bending ,binding and placing in position complete-TMT bars of Grade		works above plinth level upto floor V-level.	Cum	41.59	9302.98	386910.00
Note:- Excess/ less cement over the specified cement content used is payable/ recoverable separately. 5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting ,bending ,binding and placing in position complete-TMT bars of Grade	23.	Extra for providing richer mixes at all floor levels.	U	. "	/(
5.35.1 Providing M-30 grade concrete instead of M-25 grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting ,bending ,binding and placing in position complete-TMT bars of Grade	\					
grade BMC/RMC. (Note:- Cement content considered in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting ,bending ,binding and placing in position complete-TMT bars of Grade	1	content used is payable/ recoverable separately.				
in M-30 is @ 340 kg/cum) 24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting ,bending ,binding and placing in position complete-TMT bars of Grade						
24. Providing and mixing water proofing material in cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting bending binding and placing in position complete-TMT bars of Grade				1	111 07/	1653.0
cement concrete work in doses by weight of cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting bending binding and placing in position complete-TMT bars of Grade				n/ 41.59	111.87	4653.0
cement as per manufacturer's specification. (1 kg of water proofing material in 50 kg of cement) 25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting bending binding and placing in position complete-TMT bars of Grade	24.		1	1 1		
of water proofing material in 50 kg of cement) Kg 450.00 57.90 2605 Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. Cum 73.20 309.05 2262 Characteristics of the company		· ·	1			
25. Extra for R.C.C./B.M.C./R.M.C. work above floor V level for each four floors or part thereof. 26. Reinforcement for RCC work including straightening, cutting bending binding and placing in position complete-TMT bars of Grade			g			n
V level for each four floors or part thereof. Cum 73.20 309.05 2262 26. Reinforcement for RCC work including straightening, cutting bending binding and placing in position complete-TMT bars of Grade		of water proofing material in 50 kg of cement)	Kg	450.00	57.90	26055.0
V level for each four floors or part thereof. Cum 73.20 309.05 2262 26. Reinforcement for RCC work including straightening, cutting ,bending ,binding and placing in position complete-TMT bars of Grade	25.	Extra for R.C.C./B.M.C./R.M.C. work above floo	r	1	1	
26. Reinforcement for RCC work including straightening, cutting ,bending ,binding and placing in position complete-TMT bars of Grade				m 73.20	309.05	22622.0
straightening, cutting ,bending ,binding and placing in position complete-TMT bars of Grade	26.			(1		(
placing in position complete-TMT bars of Grade				Ì	-	-
1.10 1 1.10 1 2010.0 1 37.10 1 2010.0	1	1 - A		s 29518 0	87 18	2573380.
1		JOO D OF HIGH	1.8	2 70 10.0	7 57.15	1 20.0000

Head Draftsman

Technical Officer

Exen .

Page No: 04	u Co	nacity at N	aidkhai	
Construction of 0.55 lac Gal	llons Ca	Quantity	Allotted	Amount in
Particulars of Items	Unit	Quantity	Rate	Rs.
S.			Nato	133.
Providing & fixing of 0.63mm thick PGI sheets at				
Providing & fixing of 0.05 him thick state and lifts construction joints including all leads and lifts	3	/	000.00	10048.00 /
construction joints including an letter charge	Sqm	12.56	800.00	10046.00
complete job as directed by Engineer-in-charge 12mm cement plaster of mix 1 : 3 (1 cement : 3 fine			343.75 🖊	147468.00
	Sqm	429.00	343.73	111100.00
sand) 9 Finishing walls with water proofing cement pain	t			
of approved brand and manufacture and of	f			
of approved brand and manufacture brand required shade to give an even shade (two o	r	,	01.80	72705.00
required shade to give all even shade (sha	Sqm	792.00	91.80	12100.00
more coats)		, ,	У	
more coats Providing and fixing 1mm thick M.S. steel door wit frame of 40x40x6mm angle iron and 3mm M.S. gusse frame of 40x40x6mm angle iron and 3mm M.S. gusself frame of 40x40x6mm angle iron and 3mm angle iron and				
fittings complete, including applying a priming coat	of			6
approved steel primer.	Sam	2.56 /	4352.95	11126.00
	s. Sqm	2.00	1	1
		1		
sections, trusses and framed work applying steep hoisting, fixing in position& applying steep	el	1860.00	<i>1</i> 146.63 /	272732.00
		1000.00	1	//
	ze			
Providing and fixing hand rail of appropriate by welding etc. to steel ladder railing, balcon by welding etc. to steel ladder railing, and similar work	ny			
by welding etc. to steel ladder raining, staircase railing and similar work railing, staircase railing coat of approved steel	(S,			1
railing, staircase railing and similar including applying priming coat of approved sta	Kg	203.00	172.90	35098.00
primer. M.S tube	m) Ing	1 20011	1	. 1
	ng l			
33 Providing and fixing G.1 pipes (2) and fixing complete with G.I fittings excluding trenching complete with G.I fittings excluding trenching materials work for rising materials were supported by the complete with G.I. fittings excluding trenching work for rising materials were supported by the complete with G.I. fittings excluding trenching work for rising materials were supported by the complete with G.I. fittings excluding trenching work for rising materials were supported by the complete with G.I. fittings excluding trenching work for rising materials were supported by the complete with G.I. fittings excluding the complete with the complete wi	ain			
complete with G.I littings excluding and refilling etc (external work) for rising manner and refilling etc (external work) for rising manner and refilling etc.	nal		n	016765 00 1
and refilling etc (external work) for Hong and delivery main of OHT. 125mm dia nomin	Mt	r 100.00	2167.65	216765.00
		1		
	ing			
		í.		
and refilling etc (external work) for rising m and delivery main of OHT. 150mm dia nomi	nal	1	1	433530.00
and delivery main of OHT. Isolim and reserve	Mt	r 200.00	2167.65	433330.00
bore 35 Providing, fixing of sluice valves flanged type of	ISI			
				,
all sorts of carriages upto site of work comp		0/ 3/	14058.00	42174.00
to the ding cost of shince valves outling		1		
b miding fiving of shuice valves hanged type	e oi			
The job includes cost of fluts, be	nts,			
base incld all sorts of carriages upto sit	COL		1	60010.00
work complete job including cost of sluice va	N	0 4	17210.00	68840.00
100mm dia sluice valve		1		
37 Providing, fixing of sluice valves flanged type	olts,	•		
ISI mark. The job includes cost of nuts, b washers incld. all sorts of carriages upto si	te of			
washers incld. all sorts of carriages appearance work complete job including cost of sluice va	4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	. 1	26720.00	53440.00
150mm dia sluice valve	1	lo 2	20720.00	(
150mm dia sidice vaive		11	1	0.
		0		XT

Technical Officer

Page No: 05

Construction of 0.55 lac Gallons Capacity at Naidkhai

5.	Particulars of Items	Unit	Quantity	Allotted Rate	Amount in Rs.
0	CM O CHI win hondo of				
8	Providing and fixing of M.S fittings viz bends of				
	suitable degree, tees, collars etc to be fabricated				
	from 6mm nominal size M.S plate as per the				
	requirement of site including cost of welding. The				
	work should be leak proof and should be painted		,		n
	with anti corrosive red oxide primer. Complete	1	657.00	147.80	97117.00
	job. Mani fold, Bend, tee etc, flanged joint	Kg	657.00	147.00	3/11/.0
39	Providing and fixing of MS flanged joints (8mm to	Λ	, (/ \	
))	12mm thick) to double flanged GI/DI pipes				
	including cutting of pipes, welding charges,				
	cutting of flanges, rubber gasket, bolts, nuts				
	including testing of joint and sorts of carriages.		/ .	- 1	07100.0
	Complete Job. 125 mm dia. pipe	Joint	/ 20 //	1855.00	37100.0
10	Providing and fixing of MS flanged joints (8mm to	/	/	1	
40	12mm thick) to double flanged GI/DI pipes		- 1		
	including cutting of pipes, welding charges,				
	cutting of flanges, rubber gasket, bolts, nuts			¥	
	including testing of joint and sorts of carriages.		0	0	
	Complete Job. 150 mm dia. pipe	Joint /	′ 34 //	2150.00	73100.0
	tasting and commissioning of	/	V	X	
41	Advanced Maintenance Free environment intentity	Į /			
	Forthing system consisting of 1 no. of 3mtr length,				
	17.0 mm dia III. certified earth electrode made of night				
	tensile low carbon steel circular rods, molecularly			427	
	banded copper on outer surface (minimum copper				
	bonding thickness-250 microns) with GI terminals to connect incoming strips, (Environment friendly				
1	connect incoming strips, (Environment friendly backfill compound duly certified as per ANSI/NSF				
	standard 60/Toxic content certificate as safe for use				
	near potable ground water resources strictly as per				
1	specification enclosed. Make- HREE				
	ELECTRODES/OBO BETTERMANN / ERICO(2 Nos			l	
1	UPS and 4 Nos Main L.T Panel/2 Nos Fire Fighting	No	1.00	15800.00	15800.00
	Panel)	No	1.00/	13800.00	10000.0
1.	Providing and Fixing 25 mm x 5 mm Copper	1	7	. /	-
	Strip in 40 mm dia. G.I Pipe FRL Earth Electrode				
	including connection with Brass nut ,bolt,	,			
	spring, washer, excavation and refilling etc. as required.	RM/	60.00/	1224.00	73440.00
-	43 Supply, installation, testing and commissioning	KIVI	00.00	1221.09	7
	of lightening conductor made of 25 mm dia 300		(
	mm long copper tube having single prong at top				
1	with base plate.	Each	1.00	1500.00	1500.00
-	44 Filling available excavated earth (excluding rock)	1	/	1	
	in trenches, plinth, sides of foundation etc.	,	7		
	Layers not exceeding 20cm in depth,				
	consolidating each deposited layer by ramming		,	2	
	and watering lead upto 50m and lift upto 1.5m.	Cum	672.61	198.70	133647.00
	45 Carriage of materials by mechanical transport		7(
	including loading, unloading, stacking of materials.		1		10100 61
1	Cement/Steel Sheets for avg. lead 15kms	M.T	158.42	303.66	48102.64
		X	, ,	1 <	े 1
	\cap I ./	10	ma	1	<u> </u>
	(I W	40	4.		1
	Illand Profit	T 1.	- LI OFF	/ -	V 1965
	Head Draftsman	Tech'n	ical Officer	/ E	xph >

Page No: 06

Construction of 0.55 lac Gallons Capacity at Naidkhai

100	Constituetion of the				
S.	Particulars of Items	Unit	Quantity	Allotted Rate	Amount in Rs.
46.	Carriage of materials by mechanical transport including loading, unloading, stacking of materials. Sand/20mm agg. for avg. lead 20kms Carriage of materials by mechanical transport including loading, unloading, stacking of materials. Aggregates above 40mm for avg. lead 20kms	Cum	398.73	402.29	160405.00 10748.0¢
	Total 4% above on all items Grand Total		,		363684.00 9455776.0

Rates and quantities checked:

Head Draughtsman

Technical Officer

Executive Engineer Jal Shakti PHE Division Sopore

3 Terms and conditions:

- O1. Total value of the work is Rs.9455776.00 (Rs.Ninety four lacs fifty five thousand seven hundred seventy six only) worked out on the basis of above quoted rates which includes all taxes, levies etc and as per the drawing provided vide Chief Engineer Kashmir Jal Shakti PHE Department Srinagar's No: CE/PHE/E&T/4175-80 dated: 20-05-2022
 - O2. The date of start of the subject work shall be reckoned from the date of issuance of this allotment order, in case of failure to start the work within three days of issuance of this allotment order action as warranted shall be initiated
 - O3. An agreement shall have to be drawn by you with the department within a period of O7 days from the date of issuance of allotment, failure to execute such a formal deed shall not however prevent the contract from being enforced upon you. However payment shall not be made unless the agreement is drawn.
 - 04. Performance security equlivant to 3% of the value of the contract **Rs.283673.00** valid in accordance with bid conditions, shall have to be furnished by you in shape of CDR/BG/FDR within a week from the date of issuance of this allotment order or at the time of signing of agreement which ever is earlier.

Page No: 07 Construction of 0.55 lac Gallons Capacity at Naidkhai

All other terms and conditions and technical specifications shall the remain same as laid down in Standard bidding document of the subject E-NIT read with corrigendum minutes of Pre-bid meeting, PWD from No 25 and GFR-17.

Assistant Accounts

Officer

Technical officer

Executive Engineer

Jal Shakti PHE Division

Sopore

Copy to the:

- 01. Mission DIRCTOR Jal Javeen Mission Civil Secretariat Srinagar for favour of information.
- 02. Chief Engineer Kashmir Jal Shakti PHE Department Srinagar for favour of information.
- 03. District Development Commissioner Bandipora (Chair man DJJM) for favour of information.
- 04. Direction Palnning Jal Shakti Civil Secretariat Srinagr for favour of information.
- 05. Superintending Engineer Hydraulic Circle Baramulla/Bandipora (Member Secretary JJM) for favour of information.
- 06. Assistant Executive Engineer PHE Sub Division Sumbal for information and necessary action.
- 07. M/S WAPCOAS Ltd Corporate office 76-C intuitional area sector 18 Gurgon for information.
- 08. File Concerned.