## Jammu & Kashmir

## OFFICE OF THE EXECUTIVE ENGINEER PHE DIVISION SOPORE No:- 10903-08

M/s Mehraj Din Bhat

S/o: Khazer Mohammad Bhat

R/o: Safakadel Srinagar

Reg. No.: 109/AYY/CE/KCC/PDC/1994-95

Phone No:9797139325

E-Mail ID :Danish.mehraj26@gmail.com

Position of AAA : Accorded Position of T.S: Accorded

Retrofitting of W.S.Scheme Hamray by way of laying and fitting of pipe, construction of 2 No Pump Houses, 0.20 lac gallons Clear Water Subject: -

Sump, Chowkidar Quarter, Sluice Chamber and other allied works at

Hamray under JJMTender ID: 2022 PHE\_192737\_2).

1. Your on-line tender received in response to this office E-NIT No: Ref:

33/JJM/JSDS of 10/2022 dated: 18-10-2022.

2. Superintending Engineer Hyd. Circle Sopore's Authorization issued

vide No: SE/Hyd./14290 dated: 07-02-2023.

3. This office Letter of intent issued under No: JS/PHED/Spr/

CS/DB/10127-30 dated: 09-02-2023.

For and on behalf of Lt. Governor of Jammu and Kashmir Union Territory, contract for the work mentioned above is here by fixed with you on the following negotiated rates, terms and conditions.

	Rates:	Unit	Quantity	Allotted	Amount in
S.	Particulars of Items	e		Rate	Rs
No	Earth work in excavation by manual means in trenches	Cum	1148.00	436.00	500528.00
1	I Incine nines capies etc not chooses a				
	tor shalls wells, cospito and for				
	like not exceeding 10 Sqm on plan, depth upos 270	l	1 e	e	1
	All kinds of soil  Earth work in excavation by manual means over areas	Cum	144.74	539.35	78065.5
2	and matter 1 amili ill deputs from	i i i i i			
	(exceeding 30cm and upto 1.5mc width as well as 10 sqm on plan) including disposal of excavated earth upto 1mtr from cutting edge disposal excavated earth upto 1mtr from cutting edge disposal	13		. A	0
	excavated earth upto 1mi from cutting and soil earth to be leveled and neatly dressed. All kinds of soil	e			F1240 (
	1 11- oxcorration by inculation	cum	272.00	188.75	51340.0
3	- Land Augr arras (CACCCUIII)	1			
				1.	W HOLE
	meters and lift upto 1.5 m, as uncoted by angular			Mar I	
	Charge. in all kinds		130		0

nical Officer

Dated: - 7/2-02-2027 Advt. Cost: Rs.91.78 lacs

Allott. Cost: Rs.95.44 lacs

Time of Complt.: 90 days

Page 2nd

	W.S.Scheme Hamray	unde	r JJM		1
	W.S.Scheme Hamray	Unit	Quantity	Allotted	Amount in
S.	Particulars of Items	01110	0	Rate /	Rs.
No		L	400.00	73.05	29220.00
4	Laying and fitting of G.1 pipes complete excluding cost	Mtr	400.00	10.00	l
4			1100.00	40.80	44880.00
5	Laying and fitting of G.I pipes complete excluding cost	Mtr	1100.00	10.00	
3	of pines and earth work: 50mm dia U.1		1100.00	40.80	44880,00
6	Laying and fitting of G.I pipes complete excluding cost	Mtr	1100.00	40.00	
O	of pines and earth world 40mm dia G.I		500.00	30.65	15325.00
7	Laying and fitting of G.I pipes complete excluding cost	Mtr	500.00	30.03	
,	of pipes and earth work: 25mm dia G.I			2	
		Mtr	700.00	20.25	14175.00
8	Laying and fitting of G.I pipes complete excluding cost	With	700.00	. 0	e
	of pipes and earth work: 20mm dia G.I	L		144.40	101080.00
9	Providing and fixing G.I. pipes complete with G.I.	Mtr	700.00	144.40	101000.00
9	fittings excluding trenching and refilling etc. (external	-		0/	2
	work). 15 mm dia. nominal bore	l		20.00	241500.00
10	P/F Of 10mm thick MS Flanges To 150mm Dia GI Pipe	Job	115.00	2100.00	241500.00
10	at necessary Spots Including cost of flanges, nuts,	100	1 . 47 . 126		
	bolts, washer, welding charges, cutting of threaded				
	portion, all sorts of carriages and including the	all 3		A	
	deduction of cost of the threaded portion and excluding		V		
	laying of pipe in pipe trenches.			70	216000.00
11	P/F Of 10mm thick MS Flanges To 100mm Dia GI Pipe	Job	120.00	1800.00	216000.00
11	at necessary Spots Including cost of flanges, nuts,				
	bolts, washer, welding charges, cutting of threaded	. 4			
	portion, all sorts of carriages and including the	1.55			
	deduction of cost of the threaded portion and excluding			0 0	0
	laying of pipe in pipe trenches.	1	-		7
10		Job	120.00	1100.00	132000.00
12	at necessary Spots Including cost of flanges, nuts,				
	bolts, washer, welding charges, cutting of threaded		The same		
	portion, all sorts of carriages and including the		280	10 V	
	deduction of cost of the threaded portion and excluding	2	01		- 0 -
	laying of pine in pipe trenches.	-			
13	Making connection of G.I. distribution branch with G.I.	Eacl	h 35.00	666.25	23318.75
1.	main of following sizes by providing and fixing Tee	,			
1	including cutting and threading the pipe etc. complete			0/	10
	25 to 40 mm nominal bore	97			
14	Moleing connection of G.I. distribution branch with G.I.	. Eac	h 15.00	1268.75	19031.25
1.	less of following sizes by providing and lixing Tee	,			2920 E
	including cutting and threading the pipe etc. complete				0-
	1 50 to 80 mm nominal hore				
1	Providing and fixing C.I. Sluice valve of standard quality	y Eac	h 4.00	41000.00	164000.00
1.	ligi mort reputed make havey duty incld. Cost of	01			
	ganges nuts holts tail pieces and all other illung	s	0	1 0	, ,
	late Job 150 mm dia incld. all carriages				
1	Deviding and fixing C.I. Shuice valve of standard quality	y Eac	h 3.00	24000.00	72000.00
1	lear 1 manufod make havey dilly lilclu, cost of	ווע	1 14 1 14 8 8		
	genges buts holts tail pieces and all other fitting	s	0/0/	0-	9
	1 / I-la 100 mm dia inclu all carriages				
-	fixing C I Shince valve of Standard quant	ty Eac	ch 3.00	17000.00	51000.00
1	t make havey allo inclu, cost	OI I			
	denges pute holts tail pieces and an other ments	gs	. / .	100	2
	T T T CO man dia inclu all calliages	/		1	
-	- de cir valve isi marked includi	ng Ea	ch 2.00	5500.00	11000.00
1	- holte of cion this dicces and the			2 1 20 2	
	sorts of carriage upto site of work complete job .20mm	1		Markey 12 A	
	SULES OF CALLINGS				and the state of t

Page 3rd

	W.S.Scheme Hamray	ındeı	JJM		
		Unit	Quantity	Allotted	Amount in Rs.
S.	Particulars of Items	0	- 0	Rate	1
No	:1. QI	Frah	8.00	543.85	4350.80
19	Providing and fixing gun metal gate valve with C.I.	Each	8.00	0.0.00	
	wheel of approved quality (screwed end) 25mm nominal	12	1 00	2	1
1000	bore		7.00	704.70	4932.90
20	Providing and fixing gun metal gate valve with C.I.	Each	7.00	701.70	
	wheel of approved quality (screwed end) 40mm nominal	0	- 0-	1 e	
	bore	e	5.00	942.75	5656.50
21	Providing and fixing gun metal gate valve with C.I.	Each	6.00	942.73	3030.00
	wheel of approved quality (screwed end) 50mm nominal		1 -	, ,	0
	bore	1		150.70	040774 72
22	Filling available excavated earth (excluding rock) in	Cum	1211.75	198.70	240774.73
	trenches, plinth, sides of foundations etc. in layers not				
	exceeding 20 cm in depth, consolidating each deposited				
	layer by ramming and watering, lead upto 50 m and lift	1		1 1 1 1	0 -
	upto 1.5 m.			1	
23	Providing and laying of dry Stone soling in horizontal	Cum	86.53	816.40	70644.72
20	on level,	0	01	2	e
24	Providing and laying in position cement concrete of	Cum	29.85	4861.83	145130.49
24		1	29.00	,001.00	
	specified grade including curing but excluding the cost	1. 3.4	A.		
	of centring and shuttering. All work upto plinth level	17 00 1			
	with: 1:4:8 (1 cement : 4 coarse sand : 8 graded stone	e	1 1	l	1 0/
	aggregate 40 mm nominal size)		126 50	6978.67	952728.03
25	Providing and laying in position specified grade of		136.52	0978.07	902120.00
	reinforced cement concrete including curing but				
	excluding the cost of centering, shuttering, finishing				
	and reinforcement. All works upto plinth level. 1:2:4 (1			,	0.
	cement: 2 coarse sand: 4 graded stone aggregate 20	8	- 0	1	
	mm nominal size)		00.11	7000 76	150447.52
26	Providing and laying in position specified grade of	Cun	n 20.44	7800.76	159447.53
	reinforced cement concrete including curing but				
	excluding the cost of centering, shuttering, finishing	3			
	and reinforcement. All works upto plinth level. 1:11/2:3	3			
	(1 cement: 1½ coarse sand: 3 graded stone aggregate	e		,	
	20 mm nominal size)		0.1.10	200000	100700 70
27	Reinforced cement concrete work in walls (an	y   Cur	n 21.13	9408.13	198793.79
	thickness) including attached pilasters, buttresses	3,			
	plinth and string courses, fillets, columns, pillars	3,			
	piers, abutments, posts and struts upto floor five leve	el			
	including curing but excluding cost of centerin	g			
	abuttering finishing and reinforcement. 1:1½:3	1			
	cement: 1½ coarse sand: 3 graded stone aggregate 2	0	0/0	1 10	e
	nominal size)	**	2 2		
28	Deinforced cement concrete work in beams, suspende	d Cu	m 33.85	9849.34	333400.16
20	grand roofe having slope upto 15°, landings, balconie	s,			
	lating chaires lintels, bands, plain window sin	S,	12.0		
	and spiral stair cases upto live lev	er			,
	the cost of central	B,			7
	eniching and reinforcement with 1,172,5	( ±			- 1 Comp. 1
100	cement: 1½ coarse sand: 3 graded stone aggregate:	20	2 0	,	0
5/11	And the second of the second o	-			
	t 1 -thomas inclining situling, proppe	ng Sc	ım 617,4	8 262.30	161965.00
2	1 or over of form for, roundations, reserve	gs,			
100	bases of columns etc. for mass concrete.	3.4			
6 3 6 5	bases of columns cut, to	distribution of	10.3	10.0	120

# Page 4th W.S.Scheme Hamray under JJM

S.	Particulars of Items	Unit	Quantity	Allotted Rate	Amount in Rs
No		l	2		92137.36
30	Centering and shuttering including strutting,	Sqm	160.56	573.85	92137.30
	propping etc. and removal of form for: Walls (any	4 1			
	thickness) including attached pilasters,		S 1		
	buttresses, plinth and string courses etc.	0		75558	10040.20
31	Centering and shuttering including strutting,	Sqm	37.67	502.85	18942.36
	propping etc. and removal of form for: Lintel,				
	beams, plinth beams, girders, bressumers and			. 4	
	cantilevers.	1	e		9
32	Centering and shuttering including strutting,	Sqm	22.06	680.15	15004.1
	propping etc. and removal of form for: Columns,	•	. , .	2	
	pillars, piers, abutments, posts and struts.	1		1	l
33	Centering and shuttering including strutting,	Sqm	180.01	635.60	114414.3
	propping etc. and removal of form for: Suspended	- 1	3.7		
	floors, roofs, landings, balconies and access				
	platforms.	l	e		
34	Centering and shuttering including strutting,	Mtr	81.86	242.30	19834.6
	propping etc. and removal of form for: Edges of	11.202			3 2 1 1 7/1
	slabs and breaks in floors and walls		- 0-	e	1
35	Extra for shuttering in circular work:	Sqm	11.24	114.77	1290.0
	Foundations	1	d l	1	
36	Extra for shuttering in circular work: Walls	Sqm	130.44	52.46	6842.8
		_	32.66	127.12	4151.7
37	Extra for shuttering in circular work: Suspended	Sqm	32.00	127.12	7101.7
	floors	-	18.99	100.57	1909.8
38		Sqm	10.99	100.57	1909.0
	lintels	Sqm	12.83	48.46	621.7
39	Extra for shuttering in circular work: Edges	Sqiii	1 / 1	1	
40	Extra for every additional lift of 1.5m or part	Cum	163.21	81.65	13326.1
	thereoff.		0/0		e
4:	Pumping out water caused by springs, tidal or	KL	1224.04	155.55	190399.4
	river seepage, broken water mains or drains and		1		
	the like.		1	- L	1
43	Providing and incodporating G.P sheet for	Sqrii	16.83	650.00	10939.5
	construction joints.		l e		
4	3 Steel reinforcement for R.C.C. work including	g Kg	8053.22	87.18	702079.7
	etraightening cutting, bending, placing in	1			
	position and binding all complete above plints	1	1 / 0/	0/	/
	level Thermo-Mechanically Treated bars		80.24	270.10	20240.3
4	4 12mm Cement plaster finished with a floating	Sqm	80.24	378.12	30340.3
	coat of neat cement of mix: 1:3 (1 cement: 3	0	1	1 1/	1
	fine sand)	San	177.30	286.05	50716.6
4	5 12mm Cement plaster finished with a floating	Sqn	177.30	200.03	30710.0
	coat of neat cement of mix: 1; 4 (1 cement . 4	l		e	0
	fine sand)	Kgs		57.90	16791.0
4	6 Providing and mixing water proofing material in	rigs	290.00	37.90	1013110
	to work in doses by weight of	, .		7	(
	1 magazinacini s specification (* ***	2			100
-	of water proofing material in 50 kg of cement)				

reconical Officer

Page 5th

	W.S.Scheme Hamray	under	JJM		
	W.S.Scheme Hamiley	Unit	Quantity	Allotted	An nount in
S.	Particulars of Items	e	e	Rate	Rs.
No	C. Line trieges	Kg	8709.94	102.13	889546.17
47	Structural steel work in built up sections, trusses				
	and framed work, including cutting, hoisting, fixing in position and applying a priming coat of		, and a second		- 8-
	approved steel primer all complete. Welded	1		91.02	341388.71
48	Structural steel work in single section, fixed with	Kg	3750.70	91.02	341300.71
,,,	or without connecting plate, including cutting,				
	hoisting, fixing in position and applying a priming			0	1
	coat of approved steel primer all complete.	-d	0.68	4608.66	3133.89
49	Providing and fixing 1mm thick M.S. sheet door	Sqm	0.68	4000.00	
	with frame of 40x40x6mm angle iron and 3mm				
	M.S. gusset plates at the junctions and corners,		1 1 1 1 1 1		
	all necessary fittings complete, including applying				
	a priming coat of approved steel primer. Using				
	flats 30x6mm for diagonal braces and central	1	- 1	e	
EO	cross piece.	Cum	65.51	6802.12	445606.88
50	Brick work with common burnt clay (non-	Cum	03.51	0002.2	
	modular) bricks of class designation 7.5 in				
	foundation and plinth including curing in : Cement mortar 1:6 (1 cement : 6 coarse sand)	1	- 1		le le
51	Extra for brick work with common burnt clay	Cum	62.06	1323.65	82145.72
01	bricks/cement concrete bricks in super structure	Jum	02.00		
	above plinth level upto floor five level	0	1		
52	Providing wood work in frames of doors, windows,	Cum	1.46	46000.00	67068.00
	clerestory windows and other frames, wrought				
	framed and fixed in position with hold fast lugs or				
	with dash fasteners of required dia and length				
	(hold fast lugs or with dash fasteners shall be	^	0		1
	paid for separately): K.D Wood	0			
53	Providing and fixing panelled or panelled and	Cum	26.32	2489.75	65530.22
	glazed shutters for doors, windows and clerestory				
	windows fixing with butt hinges of required size				
	with necessary screws, excluding panelling which				
	will be paid for separately, all complete as per				
	direction of Engineer-in-charge. 30mm Second kail wood	0	1 d	2	1
54	Providing and fixing panelling or panelling and	Sqm	10.50	2360.95	24789.98
JT	glazing in panelled or panelled and glazed		10.00	2000.90	24709.90
	shutters for doors, windows and clerestory		al de la companya de		1/2
	windows (Area of opening for panel inserts				
	excluding portion inside grooves or rebates to be				
*	measured). Panelling for panelled or panelled and				
	glazed shutters 25 mm to 40mm thick. Decorative				
	ply wood both side decorative veneer (type 1)		00	,	
	conforming to IS 1328 BWR type			, e	
55	Providing and fixing panelling or panelling and	Sqm	12.01	1768.05	21234.28
	glazing in panelled or panelled and glazed		The Theory	2 1 3 11	
	shutters for doors, windows and clerestory		500	Maria de la compansión de	
	windows (Area of opening for panel inserts	10 18 1			
	excluding portion inside grooves or rebates to be				
	measured). Panelling for panelled or panelled and	1 25			
	glazed shutters 25 mm to 40mm thick. 4 mm				
	thick glass pane (weighing not less than 10	'			
	kg/sam)	TO PURE THE STATE OF	1000		

Page 6th

	W.S.Scheme Hamray	unuer	OOM	<del></del>	
S. No	Particulars of Items	Unit	Quantity	Allotted	Amount in
		0		Rate	Rs.
56	Providing and fixing wire gauze shutters using	Sqm	24.09	2966.35	71459.37
1 :	salvanized M.S. wire gauge of average width for l				
1 '	aperture 1.4 mm in both directions with wire of dia 1				
1	0.03 mm for doors, windows and clerestory windows				
- 1	marked M.S. pressed butt hinges bright				
1	misticu of required size with necessary screws as ner				
1	direction of Engineer-in-charge : 30mm Second class I	0	0		0
-	Kan wood				
	Providing corrugated G. S. sheet roofing including	Sqm	287.96	830.25	239078.79
4	The surface fixed with polymer coated I or I		1 1 1 1 1 1		
	nooks, bolts and nuts 8mm diameter with hitumen I				
	and G.I illipet washers or with G.I. limnet washers		1 - 1		
	with wille lead, including a coat of approved steel l		*		
	printed and two coats of approved paint on overlapping				
	Sincers complete lupto any nitch in harizontal/		9.7		
	tertical of curved surfacelexcluding the cost of nurling	1.10		3 3 3 3	
	and dusses and including cutting to sign and				
	shape wherever required 0.50 mm thick with gine		12.	*	1 -
58	coating not less than 2/5 gram/m2			e	
00	Providing ridges or hips of width 60cm overall width	Mtr	88.90	691.35	61461.0
	plant G.S. Sheets lixed with polymer coated I on I	The state of			
	nooks, boils and nuts 8mm dia GI limnet and	V, 14			
	bitumen washers complete. 0.63 mm thick with zinc		1/1/	1	
59	coating not less than 275 gram/m2	1			
0)	Providing and fixing 1.00mm thick coloured G.S sheet	Mtr	57.28	900.00	51552.0
60	soffit boarding incld. Supports etc complete job	1			ا ا
	Providing and fixing G.I. chain link fabric fencing of required width in mesh size 50x50 mm including	Sqm	329.40	733.50	241614.9
	strengthening with 2 mm dia wire or nuts, bolts and		1 1 4 4 3 1 1 1 4	19 1 3" "NA" A	
	washers as required complete as per the direction of				
-	Engineer-incharge.Made of G.I. wire of dia 4 mm	1	4 4		0
61	Providing and fixing plained eaves boarding. 250x32	Man	05.45	500.00	
	mm (nominal size)	Mtr	95.45	693.90	66232.7
62	Providing and fixing 1st quality ceramic glazed floor	Sam	1105	1570.07	
	tiles conforming to IS: 15622 (thickness to be specified	Sqm	14.95	1052.25	15731.1
	by the manufacturer) of approved make in all colours				
	shades except burgundy, bottle green, black of any size				
	as approved by Engineer-in-Charge in skirting risers of	r I			- 10 W
	steps and dados over 12 mm thick bed of cement	+		Charles (Section	
	Mortar 1:3 (1 cement: 3 coarse sand) and jointing with				
	grey cement slurry @ 3.3kg per sqm including pointing	,			
9	in white cement mixed with pigment of matching shade	ė			
	complete.	1	e e	1	e
63		Sqn	31.74	1161.05	200515
	conforming to IS: 15622 (thickness to be specified by	v	01.71	1101.05	36851.7
	the anufacturer), of approved make, in all colours	,	A stage in		
	shades except burgundy, bottle green, black of any size	e			
	as approved by Engineer- in-Charge, in skirting, riser	s			
	of steps and dados over 12 mm thick bed of cemen	it			
	mortar 1:3 (1 cement: 3 coarse sand) and jointin	g			
	with grey cement slurry @ 3.3 kg per sqm, including	g	."()		
	pointing in white cement mixed with pigment of	of	0-0-	0	2
	matching shade complete.	The same of the sa			1
64	Cement concrete flooring 1:2:4 (1cement: 2 coars	se Sqr	m 55.17	550.50	30371.
	sand: 4 graded stone aggregate) finished with a floating	ıg			00011.
	coat of neat cement including cement slurry and curin			1	
	complete, but excluding the cost of nosing of steps et				
	complete. 50 mm thick with 20mm nominal size stor	16			
	aggregate.		The state of the s		N

## Page 7<sup>th</sup> W.S.Scheme Hamray under JJM

15mm cement plaster on the rough side of single or half brick wall finished with a floating coat of neat cement of mix:1; 4 (1 cement: 4 fine sand)	S. No	Particulars of Items	Unit	Quantity	Allotted Rate	Amount in
half brick wall finished with a floating cost of neat cement of wix: 4 (1 cement: 4 fine sand)  Dry random rubble masonry with hard stone in foundation and plinth: With bond stone.  Supplying and fixing rolling shutters of approved make, made of required size M.S. laths, interlocked together through their entire length and jointed together at the end by end locks, mounted on specially designed pipe shaft with brackets, side guides and arrangements for inside and outside locking with push and pull operation complete, including the cost of providing and fixing necessary 27.5 cm long wire springs manufactured from high tensile steel wire of adequate strength confirming to IS:4454 part-1 and M.S. top cover of required thickness for rolling shutters.  Each 2.00 483.10 966  Providing 40x5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm diameter bolts, nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:3:6 mix (1 cement: 3 coarse sand: 6 graded stone aggregate 20 mm nominal size).  To Providing and fixing water closet squatting pan (Indian type W.C pan) with 100mm sand cast iron P or S trap, 10 litre low level PVC flushing cistern including flush pipe (of approved make) with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures compelte includng cutting and making good the walls and floors wherever required. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  To Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incid. painting of fittings and brackets cutting and making good the walls wherever required 270x420 bowed depth 178mm incid. fixtures.  Providing and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making to good of walls wherever required: White Vitreous China Flat back wash basin size 450x3		15mm	2	407.04		172135.00
60 Dry random rubble masonry with hard stone in foundation and plinth: With bond stone.  Supplying and fixing rolling shutters of approved make, made of required size M.S. laths, interlocked together through their entire length and jointed together at the end by end locks, mounted on specially designed pipe shaft with brackets, side guides and arrangements for inside and outside locking with push and pull operation complete, including the cost of providing and fixing necessary 27.5 cm long wire springs manufactured from high tensile steel wire of adequate strength confirming to IS:4454 part-1 and M.S. top cover of required thickness for rolling shutters, 80x1.25 mm M.S. laths with 1.25 mm thick top cover  68 Providing 40x5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm diameter bolts, nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:3:6 mix (1 ccment : 3 coarse sand : 6 graded stone aggregate 20 mm nominal size).  70 Providing and fixing water closet squatting pan (Indian type W.C pan) with 100mm sand cast iron P or S trap, 10 litre low level PVC flushing cistern including flush pipe (of approved make) with manually controlled device (handle lever) conforming to IS : 7231, with all fittings and fixtures compelte including cutting and making good the walls and floors wherever required. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  71 Providing and fixing sand brackets cutting and making good the walls wherever required 270x420 bowel depth 178mm incld. fixtures.  72 Providing and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White	00	half brick well finished with a floation past of neat	Sqm	421.24	402.50	172100.00
foundation and plinth: With bond stone.  Supplying and fixing rolling shutters of approved make, made of required size M.S. laths, interlocked together through their entire length and jointed together at the end by end locks, mounted on specially designed pipe shaft with brackets, side guides and arrangements for inside and outside locking with push and pull operation complete, including the cost of providing and fixing necessary 27.5 cm long wire springs manufactured from high tensile steel wire of adequate strength confirming to IS:4454 part-1 and M.S. top cover of required thickness for rolling shutters.  For Providing and fixing ball bearing for rolling shutters.  Providing 40x5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm diameter bolts, nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm I:3:6 mix (1 cement : 3 coarse sand : 6 graded stone aggregate 20 mm nominal size).  Providing and fixing water closet squatting pan (Indian type W.C pan) with 100mm sand cast iron P or S trap, 10 litre low level PVC flushing cistern including flush pipe (of approved make) with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures compete including cutting and making good the walls and floors wherever required. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever required 270x420 bowel depth 178mm incld. fixtures.  Providing and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar taps 32mm C.P brass pillar taps 32mm C.P brass pillar taps 32mm C.		cement of mix: 1:4 (1 cement: 4 fine sand)	1	- e	e	e
Supplying and fixing rolling shutters of approved make, made of required size M.S. laths, interlocked together through their entire length and jointed together at the end by end locks, mounted on specially designed pipe shaft with brackets, side guides and arrangements for inside and outside locking with push and pull operation complete, including the cost of providing and fixing necessary 27.5 cm long wire springs manufactured from high tensile steel wire of adequate strength confirming to 18:4454 part-1 and M.S. top cover of required thickness for rolling shutters. Beach 2.00 483.10 966	66	Dry random rubble masonry with hard stone in	Cum	9.45	2497.59	23601.38
Supplying and fixing rolling shutters of approved make, made of required size M.S. laths, interlocked together through their entire length and jointed together at the end by end locks, mounted on specially designed pipe shaft with brackets, side guides and arrangements for inside and outside locking with push and pull operation complete, including the cost of providing and fixing necessary 27.5 cm long wire springs manufactured from high tensile steel wire of adequate strength confirming to IS:4454 part-1 and M.S. top cover of required thickness for rolling shutters.  68 Providing 40x5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm diameter bolts, nuts and wooden plugs and embeddings in cement concrete block 30x1x15 cm 1:3:6 mix (1 cement : 3 coarse sand : 6 graded stone aggregate 20 mm nominal size).  70 Providing and fixing water closet squatting pan (Indian type W.C pan) with 100mm sand cast iron P or S trap, 10 litre low level PVC flushing cistern including flush pipe (of approved make) with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures compelte including cutting and making good the walls and floors wherever required. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  71 Providing and fixing stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever required 270x420 bowel depth 178mm incld. fixtures.  72 Providing and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap 32mm C.P brass waste of standard pattern, including painting of fittings and fixing of 80mm dia PVC vent pipes Class B  74 Providing and fixing PVC waste pipe 100mm  Mfr 15.00 400.00 6000		ioundation and plinth: With bond stone.	e	2		04500.05
through riper entire length and jointed together at the end by end locks, mounted on specially designed pipe shaft with brackets, side guides and arrangements for inside and outside locking with push and pull operation complete, including the cost of providing and fixing necessary 27.5 cm long wire springs manufactured from high tensile steel wire of adequate strength confirming to IS:4454 part-1 and M.S. top cover of required thickness for rolling shutters.80x1.25 mm M.S. laths with 1.25 mm thick top cover  Providing and fixing ball bearing for rolling shutters.  Providing fixing to frame with 10 mm diameter bolts, nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:3:6 mix (1 cement: 3 coarse sand: 6 graded stone aggregate 20 mm nominal size).  To Providing and fixing water closet squatting pan (Indian type W.C pan) with 100mm sand cast iron P or S trap, 10 litre low level PVC flushing cistern including flush pipe (of approved make) with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures compelte includng cutting and making good the walls and floors wherever required. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever required 270x420 bowel depth 178mm incld. fixtures.  Providings and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  Providing and fixing 9VC waste pipe 100mm  Mtr 15.00 400.00 6000	67	Supplying and fixing rolling shutters of approved make.	Sqm	7:64	3238.20	24739.85
end by end locks, mounted on specially designed pipe shaft with brackets, side guides and arrangements for inside and outside locking with push and pull operation complete, including the cost of providing and fixing necessary 27.5 cm long wire springs manufactured from high tensile steel wire of adequate strength confirming to IS:4454 part-1 and M.S. top cover of required thickness for rolling shutters.80x1.25 mm M.S. laths with 1.25 mm thick top cover of required thickness for rolling shutters.80x1.25 mm M.S. laths with 1.25 mm thick top cover of required thickness for rolling shutters.80x1.25 mm M.S. laths with 1.25 mm thick top cover of required thickness for rolling shutters. Each 2.00 483.10 9666 Providing and fixing ball bearing for rolling shutters. Each 78.00 163.05 12717 (and the concent of the c		through their entire length and jointed together at the				
shalt with brackets, side guides and arrangements for inside and outside locking with push and pull operation complete, including the cost of providing and fixing necessary 27.5 cm long wire springs manufactured from high tensile steel wire of adequate strength confirming to 18:4454 part-1 and M.S. top cover of required thickness for rolling shutters.80x1.25 mm M.S. laths with 1.25 mm thick top cover  68 Providing and fixing ball bearing for rolling shutters.  69 Providing 40x5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm diameter bolts, nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:3:6 mix (1 cement: 3 coarse sand: 6 graded stone aggregate 20 mm nominal size).  70 Providing and fixing water closet squatting pan (Indian type W.C pan) with 100mm sand cast iron P or S trap, 10 litre low level PVC flushing cistern including flush pipe (of approved make) with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures compelte including cutting and making good the walls and floors wherever required. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  71 Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever required 270x420 bowel depth 178mm incld. fixtures.  72 Providinbg and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing 9VC waste pipe 100mm Mtr 15.00 400.00 6000		end by end locks, mounted on specially designed pipe			y   /	
operation complete, including the cost of providing and fixing necessary 27.5 cm long wire springs manufactured from high tensile steel wire of adequate strength confirming to IS:4454 part-1 and M.S. top cover of required thickness for rolling shutters.80x1.25 mm M.S. laths with 1.25 mm thick top cover  68 Providing and fixing ball bearing for rolling shutters.  69 Providing 40x5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm diameter bolts, nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:3:6 mix (1 cement : 3 coarse sand : 6 graded stone aggregate 20 mm nominal size).  70 Providing and fixing water closet squatting pan (Indian type W.C pan) with 100mm sand cast iron P or S trap, 10 litre low level PVC flushing cistern including flush pipe (of approved make) with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures compelte including cutting and making good the walls and floors wherever required. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  71 Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever required 270x420 bowel depth 178mm incld. fixtures.  72 Providinbg and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes  74 Providing and fixing PVC waste pipe 100mm  75 Mtf 15.00 400.00 6000		shall with brackets, side guides and arrangements for				
lixing manufactured from high tensile steel wire of adequate strength confirming to IS:4454 part-1 and M.S. top cover of required thickness for rolling shutters.80x1.25 mm M.S. laths with 1.25 mm thick top cover  68 Providing and fixing ball bearing for rolling shutters.  69 Providing 40x5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm diameter bolts, nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:3:6 mix (1 cement: 3 coarse sand: 6 graded stone aggregate 20 mm nominal size).  70 Providing and fixing water closet squatting pan (Indian type W.C pan) with 100mm sand cast iron P or S trap, 10 litre low level PVC flushing cistern including flush pipe (of approved make) with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures compelte including cutting and making good the walls and floors wherever required. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  71 Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever required 270x420 bowel depth 178mm incld. fixtures.  72 Providinbg and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes  74 Providing and fixing PVC waste pipe 100mm  75 Mtf 15.00 400.00 6000		inside and outside locking with push and pull		7		
manufactured from high tensile steel wire of adequate strength confirming to 1S:4454 part-1 and M.S. top cover of required thickness for rolling shutters.80x1.25 mm M.S. laths with 1.25 mm thick top cover  8 Providing and fixing ball bearing for rolling shutters.  69 Providing 40x5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm diameter bolts, nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:3:6 mix (1 cement : 3 coarse sand : 6 graded stone aggregate 20 mm nominal size).  70 Providing and fixing water closet squatting pan (Indian type W.C pan) with 100mm sand cast iron P or S trap, 10 litre low level PVC flushing cistern including flush pipe (of approved make) with manually controlled device (handle lever) conforming to IS : 7231, with all fittings and fixtures compelte including cutting and making good the walls and floors wherever required. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  71 Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever required 270x420 bowel depth 178mm incld. fixtures.  72 Providinbg and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes  74 Providing and fixing PVC waste pipe 100mm  75 Mtf 15.00 400.00 6000		fixing necessary 27.5 are large wing and				
strength confirming to Is:4454 part-1 and M.S. top cover of required thickness for rolling shutters.80x1.25 mm M.S. laths with 1.25 mm thick top cover  68 Providing and fixing ball bearing for rolling shutters.  69 Providing 40x5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm diameter bolts, nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:3:6 mix (1 cement: 3 coarse sand: 6 graded stone aggregate 20 mm nominal size).  70 Providing and fixing water closet squatting pan (Indian type W.C pan) with 100mm sand cast iron P or S trap, 10 litre low level PVC flushing cistern including flush pipe (of approved make) with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures compelte includng cutting and making good the walls and floors wherever required. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  71 Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever required 270x420 bowel depth 178mm incld. fixtures.  72 Providing and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes  74 Providing and fixing PVC waste pipe 100mm  Mit 15.00 400.00 6000		manufactured from high tensile steel wire of adequate	W.			
cover of required thickness for rolling shutters. 80x1.25 mm M.S. laths with 1.25 mm thick top cover  68 Providing and fixing ball bearing for rolling shutters. Each 2.00 483.10 9666 providing fixing to frame with 10 mm diameter bolts, nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:3:6 mix (1 cement: 3 coarse sand: 6 graded stone aggregate 20 mm nominal size).  70 Providing and fixing water closet squatting pan (Indian type W.C pan) with 100mm sand cast iron P or S trap, 10 litre low level PVC flushing cistern including flush pipe (of approved make) with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures compelte including cutting and making good the walls and floors wherever requried. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  71 Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever requried 270x420 bowel depth 178mm incld. fixtures.  72 Providing and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes  74 Providing and fixing PVC waste pipe 100mm  Mitr 15.00 400.00 6000		strength confirming to IS:4454 part-1 and M.S. top				
Providing and fixing ball bearing for rolling shutters.  Each 2.00 483.10 966  Providing 40x5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm diameter bolts, nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:3:6 mix (1 cement: 3 coarse sand: 6 graded stone aggregate 20 mm nominal size).  70 Providing and fixing water closet squatting pan (Indian type W.C pan) with 100mm sand cast iron P or S trap, 10 litre low level PVC flushing cistern including flush pipe (of approved make) with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures compelte including cutting and making good the walls and floors wherever requried. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  71 Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever requried 270x420 bowel depth 178mm incld. fixtures.  72 Providing and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes  Class B  74 Providing and fixing PVC waste pipe 100mm  Mtr 15.00 400.00 6000		cover of required thickness for rolling shutters.80x1.25		- 0-		1
Providing 40x5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm diameter bolts, nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:3:6 mix (1 cment : 3 coarse sand : 6 graded stone aggregate 20 mm nominal size).  70 Providing and fixing water closet squatting pan (Indian type W.C pan) with 100mm sand cast iron P or S trap, 10 litre low level PVC flushing cistern including flush pipe (of approved make) with manually controlled device (handle lever) conforming to IS : 7231, with all fittings and fixtures compelte including cutting and making good the walls and floors wherever requried. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  71 Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever requried 270x420 bowel depth 178mm incld. fixtures.  72 Providing and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes  Class B  74 Providing and fixing PVC waste pipe 100mm  Mtr 15.00 400.00 6000	60	mm M.S. laths with 1.25 mm thick top cover		200	402.10	066.20
including fixing to frame with 10 mm diameter bolts, nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:3:6 mix (1 cement : 3 coarse sand : 6 graded stone aggregate 20 mm nominal size).  70 Providing and fixing water closet squatting pan (Indian type W.C pan) with 100mm sand cast iron P or S trap, 10 litre low level PVC flushing cistern including flush pipe (of approved make) with manually controlled device (handle lever) conforming to IS : 7231, with all fittings and fixtures compelte including cutting and making good the walls and floors wherever requried. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  71 Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever requried 270x420 bowel depth 178mm incld. fixtures.  72 Providinbg and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes Class B  74 Providing and fixing PVC waste pipe 100mm  Mtr 15.00 400.00 6000	08	Providing and fixing ball bearing for rolling shutters.	Each	2.00		
including fixing to frame with 10 mm diameter bolts, nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:3:6 mix (1 cement : 3 coarse sand : 6 graded stone aggregate 20 mm nominal size).  70 Providing and fixing water closet squatting pan (Indian type W.C pan) with 100mm sand cast iron P or S trap, 10 litre low level PVC flushing cistern including flush pipe (of approved make) with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures compelte including cutting and making good the walls and floors wherever required. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  71 Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever required 270x420 bowel depth 178mm incld. fixtures.  72 Providinbg and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes Class B  74 Providing and fixing PVC waste pipe 100mm  Mtr 15.00 400.00 6000	69	Providing 40x5 mm flat iron hold fast 40 cm long	Each	78.00	163.05	12717.9
cement concrete block 30x10x15 cm 1:3:6 mix (1 cement: 3 coarse sand: 6 graded stone aggregate 20 mm nominal size).  70 Providing and fixing water closet squatting pan (Indian type W.C pan) with 100mm sand cast iron P or S trap, 10 litre low level PVC flushing cistern including flush pipe (of approved make) with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures compelte including cutting and making good the walls and floors wherever requried. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  71 Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever requried 270x420 bowel depth 178mm incld. fixtures.  72 Providinbg and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes Class B  74 Providing and fixing PVC waste pipe 100mm  Mtr 15.00 400.00 6000		including fixing to frame with 10 mm diameter				
cement: 3 coarse sand: 6 graded stone aggregate 20 mm nominal size).  70 Providing and fixing water closet squatting pan (Indian type W.C pan) with 100mm sand cast iron P or S trap, 10 litre low level PVC flushing cistern including flush pipe (of approved make) with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures compelte including cutting and making good the walls and floors wherever required. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  71 Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever required 270x420 bowel depth 178mm incld. fixtures.  72 Providinbg and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes Class B  74 Providing and fixing PVC waste pipe 100mm  Mfr 15.00 400.00 6000				<b>1</b>		
20 mm nominal size).  70 Providing and fixing water closet squatting pan (Indian type W.C pan) with 100mm sand cast iron P or S trap, 10 litre low level PVC flushing cistern including flush pipe (of approved make) with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures compelte including cutting and making good the walls and floors wherever requried. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  71 Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever requried 270x420 bowel depth 178mm incld. fixtures.  72 Providinbg and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes Class B  74 Providing and fixing PVC waste pipe 100mm  Mfr 15.00 400.00 6000			62.0			
Providing and fixing water closet squatting pan (Indian type W.C pan) with 100mm sand cast iron P or S trap, 10 litre low level PVC flushing cistern including flush pipe (of approved make) with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures compelte including cutting and making good the walls and floors wherever required. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  71 Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever required 270x420 bowel depth 178mm incld. fixtures.  72 Providinbg and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes Class B  74 Providing and fixing PVC waste pipe 100mm  Mfr 15.00 400.00 6000			0	_ 0 _	e	
[Indian type W.C pan] with 100mm sand cast iron P or S trap, 10 litre low level PVC flushing cistern including flush pipe (of approved make) with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures compelte including cutting and making good the walls and floors wherever requried. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  71 Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever requried 270x420 bowel depth 178mm incld. fixtures.  72 Providinbg and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes Class B  74 Providing and fixing PVC waste pipe 100mm  Mfr 15.00 400.00 6000	70		Foob	1.00	5534.80	5534.80
P or S trap, 10 litre low level PVC flushing cistern including flush pipe (of approved make) with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures compelte including cutting and making good the walls and floors wherever required. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  71 Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever required 270x420 bowel depth 178mm incld. fixtures.  72 Providing and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes  74 Providing and fixing PVC waste pipe 100mm  Mtr 15.00 400.00 6000	10			1.00	3334.60	3331.0
including flush pipe (of approved make) with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures compelte including cutting and making good the walls and floors wherever required. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  71 Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever required 270x420 bowel depth 178mm incld. fixtures.  72 Providinbg and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes Class B  74 Providing and fixing PVC waste pipe 100mm  Mtr 15.00 400.00 6006						
manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures compelte including cutting and making good the walls and floors wherever requried. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  71 Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever required 270x420 bowel depth 178mm incld. fixtures.  72 Providing and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes Class B  74 Providing and fixing PVC waste pipe 100mm  75 Mtr 15.00 400.00 6000						
fixtures compelte including cutting and making good the walls and floors wherever requried. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  71 Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever required 270x420 bowel depth 178mm incld. fixtures.  72 Providinbg and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes  Class B  74 Providing and fixing PVC waste pipe 100mm  Mtr 15.00 400.00 6000			11 10 10 20 11 11 11 11			
good the walls and floors wherever required. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  71 Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever required 270x420 bowel depth 178mm incld. fixtures.  72 Providinbg and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes  Class B  74 Providing and fixing PVC waste pipe 100mm  Mtr 15.00 400.00 6000						
White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests  71 Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever requried 270x420 bowel depth 178mm incld. fixtures.  72 Providinbg and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes Class B  74 Providing and fixing PVC waste pipe 100mm  Mtr 15.00 400.00 6000						
size 580x440 mm with intergal type foot rests  71 Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever requried 270x420 bowel depth 178mm incld. fixtures.  72 Providinbg and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes Mtr 3.30 250.00 825 Class B  74 Providing and fixing PVC waste pipe 100mm Mtr 15.00 400.00 6000		good the walls and floors wherever required.				
71 Providing and fixing stainless steel A ISI 304, (18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever required 270x420 bowel depth 178mm incld. fixtures.  72 Providinbg and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes Class B  74 Providing and fixing PVC waste pipe 100mm  75 Mtr 15.00 400.00 6000		White vitreous china orrisa pattern W.C Pan of		11	0	e
(18/8) Kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever requried 270x420 bowel depth 178mm incld. fixtures.  72 Providinbg and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes Class B  74 Providing and fixing PVC waste pipe 100mm  Mtr 15.00 400.00 6000		size 580x440 mm with intergal type loot rests	Each	3.00	3193.15	9579.4
brackets and stainless steel plug 40mm incld. painting of fittings and brackets cutting and making good the walls wherever required 270x420 bowel depth 178mm incld. fixtures.  72 Providinbg and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes Class B  74 Providing and fixing PVC waste pipe 100mm  Mtr 15.00 400.00 6000	71	Providing and fixing staffiess steel A lot 50%,	Dacii	0.00	0150.10	5075.1
painting of fittings and brackets cutting and making good the walls wherever required 270x420 bowel depth 178mm incld. fixtures.  72 Providinbg and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes Mtr 3.30 250.00 825 Class B  74 Providing and fixing PVC waste pipe 100mm Mtr 15.00 400.00 6000		brackets and stainless steel plug 40mm incld.				
making good the walls wherever required 270x420 bowel depth 178mm incld. fixtures.  72 Providinbg and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes Mtr 3.30 250.00 825 Class B  74 Providing and fixing PVC waste pipe 100mm Mtr 15.00 400.00 6000		painting of fittings and brackets cutting and	19 C. PA			
270x420 bowel depth 178mm incld. fixtures.  72 Providinbg and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes Class B  74 Providing and fixing PVC waste pipe 100mm  Mtr 15.00 400.00 6000		making good the walls wherever required			1	-
72 Providinbg and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes Class B  74 Providing and fixing PVC waste pipe 100mm  75 Mtr 15.00 400.00 6000		270×420 howel depth 178mm incld. fixtures.	Valuation.		075000	2007
waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes Class B  74 Providing and fixing PVC waste pipe 100mm  Mtr 15.00 400.00 6000	72	Providing and fixing wash basin C.I brackets	, Each	3.00	2769.20	8307.6
fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes Mtr 3.30 250.00 825 Class B  74 Providing and fixing PVC waste pipe 100mm Mtr 15.00 400.00 6000		15mm C.P brass pillar taps 32mm C.P brass	6			
of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes Mtr 3.30 250.00 825 Class B  74 Providing and fixing PVC waste pipe 100mm Mtr 15.00 400.00 6000		waste of standard pattern, including painting of				
Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes Mtr 3.30 250.00 825 Class B  74 Providing and fixing PVC waste pipe 100mm Mtr 15.00 400.00 6000		fittings and brackets cutting and making the good	i			
single 15mm C.P brass pillar tap  73 Providing and fixing of 80mm dia PVC vent pipes Mtr 3.30 250.00 825  Class B  74 Providing and fixing PVC waste pipe 100mm Mtr 15.00 400.00 6000		of walls wherever required. White videous office	n			
73 Providing and fixing of 80mm dia PVC vent pipes Mtr 3.30 250.00 620 Class B  74 Providing and fixing PVC waste pipe 100mm Mtr 15.00 400.00 6000		: 1- 15mm C P brass pillar tap		1/1		
Class B 74 Providing and fixing PVC waste pipe 100mm Mtr 15.00 400.00 6000	77	Providing and fixing of 80mm dia PVC vent pipes	s Mtr	3.30	250.00	825.0
74 Providing and fixing PVC waste pipe 100mm	173			1		l l
77 1107.00 00 0007/	7/	Providing and fixing PVC waste pipe 100mm	Mtr	15.00	400.00	6000.0
1.5 in PVC waste nine 80mm   Mtr   80.20   350.00   28070	1 12	1.5 to DVC weste nine 80mm	Mtr	80.20	350.00	28070.0
75 Providing and fixing PVC waste pipe 80mm Mtr 80.20 350.00 28070	75	Providing and lixing PVC waste pipe domini				

chnical Officer

	Page 8 <sup>th</sup> W.S.Scheme Hamray	unde	er J	JM		Amount in Rs.
	W.S.Scheme Hamray	Unit	TC	uantity	Allotted	Amount in 710
T	Particulars of Items	Offic		1	Rate	
	Tartiodials of Rem	l	-	11.00	349.95	3849.45
	Comproved quality	Each		11.00	- 0	2633.10
1	Providing and fixing of C.P Bib taps of approved quality		1	- 00°	438.85	2633.10
		Each		6.00	400.00	0
	Providing and fixing of of ball valves/Gate valves (brass)	1.54		,	e	
	of approved quality high or low pressure with plastic	e			1200.00	1200.00
1	floots complete	Each	1	1.00	1200.00	
	Providing and fixing of cowl for vent pipe (80mm)	Luci	6	100	200.00	200.00
	U -duper PVC for	Each	1	1.00	200.00	
)	Providing and fixing of 100-80mm dia reducer PVC for	144	1	e	536.10	1072.20
	went nine	Each	1	2.00	530.10	
)	Providing and fixing of C.P brass Angle valve	1 1 1 3 1 1	0	200	285.00	1140.00
		Eacl	1	4.00	, ,	77110 15
1	Providing and fixing of soap dish		_ 9	86.80	431.10	37419.48
	G. J. ripps complete with G.I	Mtr		86.80	1021-4	
2	Providing and fixing of G.I pipes complete with G.I		_0_	100.00	182.65	22502.48
			1	123.20	102.00	
3	Providing and fixing of G.I pipes complete with G.I			1	120.00	720.00
		Eac	h	6.00	120.00	
34	Providing and fixing of bends with excess- door 80mm	100	0	1	180.00	180.0
,	Clarity with excess door 100mm	Eac	h	1.00	1 1	100.7
35	Providing and fixing of bends with excess- door 100mm		ex	329.40	188.80	62190.7
	Finishing with Epoxy paint (two or more coats) at al	Sqr	n	329.40	100	
86						
	specifications including appropriate priming coat	,		- 1	- l	1
	specifications including appropriate printing appropriate on steel work	10 6 6	e		91.80	16472.5
	preparation of surface, etc complete. On steel work	f Sqi	m	179.44	91.00	
87	Finishing walls with water proofing cement paint of			0		0
	Finishing walls with water probling control required shade on New work (two or more coats applie		1		50.05	10649.7
	@ 3.84 kg/10sqm)	of Sq	m	179.44	59.35	100.2
88	(a) 3.84 kg/10sqm)  Applying one coat of water thinnable cement primer of the state		1		70	3692.5
	Applying one coat of water thinhelds approved brand and manufacture on wall surface.	y Sq	m	62.06	59.50	3072.0
89	approved brand and manufacture on war out or gree Applying priming coat:With ready mixed pink or gree Applying priming coat:With ready manufacture on wood manufacture on war out of the wood manufacture of war of the wood war of the	d		American Services	1	1
0.	primer of approved brand and maradas	~	P			7568.2
	work (hard and soft wood)	d So	m	62.06	121.95	/500.2
9		re Dy				L
יכ	and manufacture to give all even shades		1	1		=======================================
	coats on new work	of Sc	m	321.60	172.40	55443.8
9	- I white cement based party	or De	1111			
9	Providing and applying white control as specified thickness, of approved brand as specified thickness, the playered wall surface	to			0 -	1
			1	/1	1	
-	manufacturer, over the plastice with manufacturer, over the plastice prepare the surface even and smooth complete.	of S	qm	321.60	149.05	47934.4
-	prepare the surface even and smooth compression.  Distempering with oil bound washable distemper to give an even and manufacture to give an even and manufacture to give an even and manufacture.	en   St	1			
ا ا	Distempering with oil bound washable approved brand and manufacture to give an every approved brand and manufacture to give an every approved by the control of the control	nd				
1	approved brand and manufacture to give an shade on New work (two or more coats) over a shade on New work with water thinnable ceme	ent		1		1
	shade on New work (two or more coats) shade including priming coat with water thinnable ceme			1		
	nrimer holto	ISI F	ach	8.00	229.90	1839.2
1	primer  Providing and fixing aluminum sliding door bolts  providing and fixing aluminum sliding door bolts	ide	4011			
1	Providing and fixing aluminum shaing door marked anodized (anodic coating not less than gramarked anodized (anodic requirement or dyed to requirement)	red		***		
	marked anodized (anodic coating not less than general AC 10 as per IS: 1868) transparent or dyed to requi	e				0 1
	AC 10 as per IS: 1868) transparent of dyea to require colour or shade with nuts and screws etc. complete	~	l	1		1
1	250v16 mm	red E	ach	84.00	57.35	4817.4
-	250x16 mm  Providing and fixing aluminum tower bolts ISI mar.	ac E	acii	300		
	Providing and fixing aluminum tower botts for an anodized (anodic coating not less than grade AC 10 anodized (anodic coating not dyed to required colou	as		1 1 1 1 1 1 1 1 1		
1	anodized (anodic coating not less than grade its anodic coating not less than grade its another less than grade its anodic coating not less than grade its anodic coating n	-10			0	1
1	per IS: 1868) transparent or dyed to required established with necessary screws etc. complete: 100	X10			al al	
	shade with necessary	1 1 7	) 1-	16.00	89.20	1427.2
	mm  95 Providing and fixing aluminum tower bolts ISI mar	кеа   Е	Cach	10.00	09.20	
	Providing and fixing aluminum tower botts for that anodized (anodic coating not less than grade AC 10 anodized (anodic coating not less than grade AC 10 anodized (anodic coating not less than grade AC 10 another parent or dyed to required colours)	as		7		
	adjaced (anothe Coating and colonial co	ror			3 11 1	
- 1	per IS: 1868) transparent or dyed to required color shade with necessary screws etc. complete: 200	XIO			1.0	
	The second critical contraction of the second contraction of the secon					

Page 9th

	W.S.Scheme Hamray	ınder		Allotted	Amount in Rs.
A STATE OF THE PARTY OF THE PAR	Particulars of Items	Unit	Quantity	Rate	· ·
)		Anne de la constante	15:00	66.35	995.25
5 1	PRODUCTION CONSIST THE CONTRACT OF THE PROPERTY OF THE PROPERT	Bach	15:00	00.00	
	inodized (anadia agating not less than glade of the				
			9		
	and shade with necessary screws etc. complete. 125	A	1 1	e	January Comments
1	77 177	and the second	44.00	52.30	2301.20
P7	Providing and Grieg obuminum handles ISI marked	Each	44.00		100 mg
'	onodinad forestin senting and 1988 IIIIII RIBUS (1987)				
	and the theory and the most the most in reduced water to			C)	1
	and shade with necessary screws etc. complete. 100		·	1	- Company of the Comp
1	133 133	manie Mariana	2000.00	13.00	26000.00
98	Providing & Gying on Terrace ( at all floor levels)	Litre	2000.00		
90	malusthalina water storage ISBK ISI 12/VI				aprilips of the
	indicating the DIQ license no. With cover and sures I				
	lealing arrangement and making necessary notes to			经证金 化二烷	
	inlet putlet and over flow pipes but without fittings are		All All		0
	the base support for tank ( sintex, Electroplast, Star,	10000	le		and the second s
	1 attra or agriculant having valid ISI license.		3.00	8000.00	24000.00
99	District of numb House by providing	Job	3.00	1	
33	fixing /fittings of switches, boxes, Boards, MCB etc. of				
	standard qualities ISI mark etc (complete job)	Daint	19.00	2000.00	38000.00
100	of pump House by providing	Point	19.00	1	1
100	fixing / fittings of Heating points incld. all accessories	Point	13.00	1500.00	19500.00
101	Flectrification of pump House by providing		15.00	V	1 1 1/4
101	fixing/fittings of Lightening points incld. all		ee	0	18000.00
		Mtr	120.00	150.00	18000.00
102	Providing and fitting of service line 1/10 of specimen	IVICI		1 2 2 2 2 2	
10.	specification complete job			1	1
10:			1	- 00	
1	different sources to hearest dampares	d	1 1	050.00	30233,30
	- Toding unioning	Cun	n 84.22	358.98	
10	4 i) Stone soiling/Stone for avg. lead 1211111		25.85	437.30	11304,21
	5 ii) Stone agg. 40mm for avg. lead 20kms	Cur	n 25.65		83072.89
10	5 III Stone agg. 40mm to 5	Cur	n 206.50	402.29	83072.03
10	6 iii) Stone agg. 20mm for avg. lead 20kms		1	402.29	59116.52
10	Lod 20kms	Cui	•		
10	7 iv) Sand for avg. lead 20kms	M.	123.30	249.65	30781.85
	(Cteal for avg lead 10 kms				
10	v) Cement/Steel for avg. road	M.	1 28.34	2 357.63	
1	09 vi) Pipes for avg. lead 20kms		42783.	0. 2.53	108240.99
1	Source Lead 75km	N	1 1	-	1
1	10 vii) Bricks for avg. lead 75km	M	2.12	356.71	756.23
	11 viii) C.G.I sheets for avg. lead 5kms	1	2		8160.03
1		nt   M	17.43	400.10	0
1	12 Carriage of pipes by Manual Ross.	ng			
1	Carriage of pipes by Manual labour from the sources to nearest dumping site of work including loading, unloading for avg. lead 750Mtrs  Tot		1		9177735.6
	loading, unloading for avg. read.	al			367109.0
	Above 4% on all iter	MANAGEMENT STREET, STR			and the same of
	Above 470 on an account	Appellation by Audionomics	and the second of the second o	A District of the Control of the Con	9544845.0
-	Allotted Co		de la contrata del contrata de la contrata del contrata de la contrata del la contrata de la contrata del la contrata de la co		

Rates and quantities checked:

Head Draughtsman

Technical Officer

Executive Engineer
Jal Shakti PHE Division

### W.S.Scheme Hamray u.

- Total amount of the work should in no case exceed beyond Rs.9544845.00 (Rs.Ninety five lacs forty four thousand eight hundred and forty five only) which includes all Terms and conditions:
- 2. The work shall have to be completed by you within a period of 90 days failing which the panality under rules shall be imposed upon you.
- 3. Performance security @ 3% of allotted cost i,e Rs.286345.00 in shape of CDR/BG/FDR shall have be deposited by you in this office within seven days from the date of issue of this allotment from this office failing which action shall be initiated as per SBD of the
- 4. An agreement shall have to be drawn by you with the department within a period of 07 days from the date of issuance of allotment, failure to executed such a formal deed shall not however prevent the contract from being enforced upon you. However payment on account of this work shall not be considered in absence of agreement.
- 5. The earnest money amounting to Rs.183600/= deposited by you in this office as a bid security against the contract vide CDR No: 3240575 dated: 16-01-2023 shall be considered for release once the performance security @ 3% of allotted amount is
- 6. The allotted work shall have to be monitored by Third Party Monitoring Agency (WAPCOAS) appointed by the department.
- 7. All other terms and conditions shall remain same as laid down in E-NIT/ Standard bidding document/PWD from No 25 and GFR-2017.

ccounts Assistan

Technical officer

Executive Engineer al Shakti PHE Division

#### Copy to the:

- Chief Engineer Kashmir Jal Shakti PHE Department Srinagar for favour of information.
- District Development Commissioner Baramulla (Chair person DJJM) for favour of information.
- Superintending Engineer Hydraulic Circle Baramulla/Bandipora (Member Secretary JJM) for favour of
- iv) Assistant Executive Engineer PHE Sub Division Sopore for information and necessary action.
- M/S WAPCOAS Ltd Corporate office 76-C intuitional area sector 18 Gurgon for information.
- vi) File Concerned.