Jammu & Kashmir

OFFICE OF THE EXECUTIVE ENGINEER PHE DIVISION SOPORE

M/s Ms. Teli Constructions Prop: Mr. Ali Mohammad Teli R/o: Mohalla Teeliyan Sopore

Reg. No.: SE/Hyd /Sopore/17(Seveenteen)/AAY/Civil/Sanitary 2010-11

Phone No: 9797040101

Position of AAA: Accorded Position of T.S: Accorded

No: 10003-00 Dated:06-02-2023 Advt. Cost: Rs.63.96 lacs Allott. Cost. Rs.65.10 lacs Time of Complt.: 90 days

Retrofitting of W.S.Scheme Harwan by way of laying & fittings of Subject: various dia pipes, construction of 0.10 lac Gallon SR & allied works

under JJM (Tender ID: 2022 PHE_192737_7).

1. Your on-line tender received in response to this office E-NIT No: Ref:

33/JJM/JSDS of 10/2022 dated: 18-10-2022 S.No: 7.

2. Superintending Engineer Hyd. Circle Sopore's Authorization issued

vide No: SE/Hyd./DB/12729-41 dated: 07-01-2022

3. This office Letter of intent issued under No: JS/PHED/Spr/CS/DB

9065-68 dated: 10-01-2023.

For and on behalf of Lt. Governor of Jammu and Kashmir Union Territory, contract for the work mentioned above is here by fixed with you on the following negotiated rates, terms and conditions.

S.	Particulars of Items	Unit	Quantity	Allotted Rate /	Amount in Rs.
No 1	Earth work in excavation by manual means in trenches for foundations, drains, pipes, cables etc. (not exceeding 1.5 m in width) and for shafts, wells, cesspits and the like not exceeding 10 sqm on plan, including dressing of sides and ramming of bottoms lift upto 1.5 m, including getting out excavated earth and disposal of surplus excavated upto 1mt from cutting edge earth as directed:	cum	1032.43	436.00	450140.35
2	Earth work in excavation by mechanical means over areas (exceeding 30cm and up[to 1.5mtr in depth, 1.5mtr in width as well as 10 sqm on plan) including disposal of excavated earth upto 50m from cutting edge disposal earth to be levelled and neatly dressed. All kinds of soil	eûm	516.21	252.05	130110.73

cal Officer

Page No: 2nd

1	W.S.Scheme Harwan	inder J	JM		
5	Particulars of Items	Unit	Quantity	Allotted	A second
10		0	0	Rate (Amount in
Ear	rth work in excavation by manual means in	cum	1032.43	Constitution of the Consti	Rs.
tre	enches for foundations, drains, pines, cables	Cum	1032.43	646.05	667001.40
etc	e. (not exceeding 1.5 m in width) and for shafts,			100	
We	ells, cesspits and the like not exceeding 10 sqm			, ,	
on	n plan, including dressing of sides and ramming				
of	bottoms lift upto 1.5 m, including getting out	1.00			Za Timber
01		10.0			
			17		
ez	xcavated upto 1mt from cutting edge earth W.	0	0	0	
- Indiana	3.Macadem	2	<u> </u>		
4 E	Earth work in bulk excavation by manual means	cum	301.75	539.35	162749.80
0	over areas (exceeding 30 cm in depth, 1.5 m in				
V	width as well as 10 m2 on plan) including				
(disposal of excavated earth lead upto 50 meters	,	n 1x 1 2 ,	17	
1	and lift upto 1.5 m, as directed by Engineer-in-	0	2	0	0
	Charge.	\ \lambda	L		
5	Dismantling of GI pipe including earthwork	m	350.00	110.65	38727.50
	excavation, removing of pipe, stacking within				
	50m lead and refilling of trenches complete (Above		0	0	0
	40mm)	l	1	L.	44887.50
6	Dismantling of GI pipe including earthwork		450.00	99.75	44887.50
Ŭ	excavation, removing of pipe, stacking within		11/1-1		
	50m lead and refilling of trenches completebelow		0	0	0
	10	· L	2500.00	95.28	238200.00
7	Laying and fitting of G.I pipes complete including	g m	2500.00	90.20	0
	pipe fittingss65mm	S		2	43725.00
1-0	Laying and fitting of G.I pipes complete including	g m	750.00	58.30	43723.00
8	sing fittings 50mm	<i>y</i>	2		199363.00
	Laying and fitting of G.I pipes complete including	g m	3650.00	54.62	199303.00
9	10mm	1	100000	39.10	39100.00
-	1 String of G I pines complete including	g m	1000.00	39.10	09100.00
10	· Catings 25mm	V	0	26.76	52182.00
1	1 Stting of G I pipes complete including	g m	1950.00	20.70	02102.00
1	· Cittle as Olmm		2	25.40	71323.20
	1 String of G I pipes complete including	g m	2808.00	25.40	0
1	15mm	/		1100.00	385000.00
	LI MC Florage TO SUITIN DIA	I job	350.00	1100.00	363000.00
	P/F of 10mm thick MS Flanges To community Pipe at necessary Spots Including cost of flanger Pipe at necessary Spots Including charges, cutting the spots of the pipe at necessary Spots Including charges, cutting the pipe at necessary Spots Including charges.	5,			
	Pipe at necessary Spots metading cost of nuts, bolts, washer, welding charges, cutting nuts, bolts, washer, welding charges and carriages and carriages and carriages and carriages and carriages.	01			
	nuts, bolts, washer, weiding charges, threaded portion, all sorts of carriages and threaded portion of cost of the threaded	d		8,5	
	threaded portion, all soits of carried including the deduction of cost of the threaded including the deduction of cost of pipe in pipe in pipe.	ne 1		0	0
	portion and excluding laying of pro-	1			142200.00
	trenches. 80mm dia	to job	158.00	900.00	142200.00
1	14 Providing and fixing of 10th thek monages	,			_
	Gi pipes incl cutting of pipes, incl of and all sorts of carriage nuts, bolts, RI cloh and all sorts of carriage	of /	2 0	1	Q
	pipes complete job 65mm ø G.l =		70.00	800.00	56000,00
	pipes complete job 65mm & G.1 15 Providing and fixing of 10m thick MS flanges incl c/o flanges	to job	70.00		
	Providing and fixing of foll thick in C/o flanger Gi pipes incl cutting of pipes, incl c/o flanger all sorts of carriage	of l			
	holte Ri clon and an sorte	01		-	
	pipes complete job 50mm ø G.1 =	and the second second second second second	The second second second second second		
					M

Head Draftsman

			Particulars of Items	Unit	Quantity	Allotted	Amount in
	5			e	e	Rate 4	Rs.
	10	willin	g available excavated earth (excluding rock)	cum	2458.38	198.70	488480.34
	10	in tr	enches, plinth, sides of foundations etc. in	5/2			
		lover	s not exceeding 20 cm in depth, onsolidating	A la ekipe Gaz			
		each	deposited layer by ramming and watering,	0	0	0	0
		lead	upto 50 m and lift upto 1.5 m.	X	X	· · · · · · ·	<u> </u>
_		Mak	ting connections of G distribution branch with	Each	20.00	666.25	13325.00
	17	GL	main of following size by providing and fixing				
		Tee	including cutting and threading the pipe etc	1	0	Φ	1
		con	uplete 25 to 40mm nominal bore	X	K	· · · · · · · · · · · · · · · · · · ·	6010.75
-	18	Ma	king connections of G distribution branch with	Each	5.00	1268.75	6343.75
	10	GI	main of following size by providing and fixing				
		Ter	e including cutting and threading the pipe etc	0	.0	0	1
		con	mplete 50 to 80mm nominal bore	1	075.00	180.00	49500.00
+	19	M	anufacturing providing and fabrication of	Kg	275.00	180.00	1,000.00
1	13	NA	e ici bend TEES as per various gound				
1			refile nine specials at site made out of GI/MS				
1		ni	ne incl. c/o nine flanges, nuts, bolts, Ri cloth				
-		a	nd all sorts of carriage upto site of work	D		Q.	2
		C	omplete job 80mm	Each	75.00	40.00	3000.00
	2	0 R	dethreading of damaged ends of various dia pipes		5.00 🌡	24000.00	120000.00
	2	1 F	Providing and fixing C.I Sluice valve of standard quality	job 🕖	5.00	21000.00	
	1	1 -	at all make havey filly filling, cook of				
		1	langes nuts, bolts tail pieces and all other fittings complete Job.100 mm dia. incld. all carriages		· L	17000.00	51000.00
	-		and fixing (1 Shince valve of standard	job /	3.00	17000.00	51000.00
		22	is tot mort reputed make have duty inclu-				
			of denges puts holts fall pieces and an other		march to		
			fittings complete Job.80 mm dia.incld. all	2	0	0	
			그 생생님 그 그녀는 그 그렇다는 그 사람들은 사람들이 되었다. 그는 사람들이 되었다면 하는 사람들이 되었다면 하는 사람들이 되었다.		4.00	5500.00	22000.00
		23	Providing and fixing of air valve ISI marked including c/o flanges ,nuts ,bolts ,RI cloth , tail				
			pieces and all sorts of carriage upto site of work	1			0
			-1sts ish 20mm incld all carriages		-	2502.00	218750.00
	1	24	The devine and fixing /101111111g (fich into	m	87.50	2500.00	210730.00
		24	nine NP3 TVDE IIICIUUIIIS				
			the arrange of trenches as specified to	Sec. 15. 11. 11. 11. 11.			
			traffic load including same				
			coushioning by 2nd class sand and cost of pipe. The job includes all sorts of carriage upto site of the job includes all sorts of carriage upto site of the job includes all sorts of carriage upto site of the job includes all sorts of carriage upto site of the job includes all sorts of carriage upto site of the job includes all sorts of carriage upto site of the job includes all sorts of carriage upto site of the job includes all sorts of carriage upto site of the job includes all sorts of carriage upto site of the job includes all sorts of carriage upto site of the job includes all sorts of carriage upto site of the job includes all sorts of carriage upto site of the job includes all sorts of the job includes all sorts of carriage upto site of the job includes all sorts of th				
			work complete job (TO BE UTILISED AS	3	0	0	
			OLEEVEC)		1	2005 60	41346.40
		25	Cutting of road and making good the same incl al	l cum	12.29	3365.60	41240,40
		20	to complete the 100	1 1000	30.65	816.40	25020.11
		26	Providing and laying stone soling hand packed on level		1		*
		27	Providing and laying in position cement concrete of	of cum	12.22	4861.84	59415.53
		21	The desired of the land of the country of the count	36			
			of contring and chuttering All Work upto pilitin levi		A 18 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		1
			with:1:4:8 (1 cement : 4 coarse sand : 8 graded stor aggregate 40 mm nominal size)	1	0	l l	F4170 22
		28	Providing and laying in position cement concret	te cun	n 8.38	6465.20	54178.33
		28	of specified grade including curing but excluding	18			
			the cost of centring and shuttering. All work up	to			
			plinth level with: 1:2:4 (1 cement : 2 coarse sand				
			4 graded stone aggregate 20 mm nominal size)			100	0
							9

Head Draftsman

Page No: 4th

	W.S.Scheme Harwan			T	
15	Particulars of Items	Unit	Quantity	Allotted	Amount in Rs.
No	The second secon	1	1	Rate /	e
29	Providing and laying in position specified grade of	cum	2.88	6978.68	20098.58
	reinforced cement concrete including curing but				
	excluding the cost of centering, shuttering,				
	finishing and reinforcement. All works upto plinth				
	level. 1:2:4 (1 cement : 2 coarse sand : 4 graded	0	0	Q	2
	stone aggregate 20 mm nominal size) Providing and laying in position specified grade of	cum	13.43	7800.76	104764.21
30	reinforced cement concrete including curing but	Cum	10.40	7000.70	101701.21
	excluding the cost of centering, shuttering,				
	finishing and reinforcement. All works upto plinth				
	level.1:1½:3 (1 cement : 1½ coarse sand : 3	7	1	0	1
	graded stone aggregate 20 mm nominal size)	1	-	2	. A
31	Reinforced cement concrete work in walls (any	cum	22.02	9408.14	207211.36
O1	thickness) including attached pilasters, buttresses,				
	plinth and string courses, fillets, columns, pillars,				
	piers, abutments, posts and struts upto floor five level including curing but excluding cost of centering				
	shuttering, finishing and reinforcement. 1:1½:3 (1				
	cement: 1½ coarse sand: 3 graded stone aggregate 20	1	0	0	0
	mm nominal size)	L	14.25	9849.35	141296.61
32	Reinforced cement concrete work in beams, suspended floors roofs having slope upto 15°,	cum	14.35	9049.33	111230.01
	floors, roofs having slope upto 15°, landings, balconies, shelves, chajjas, lintels, bands,				
	plain window sills, staircases and spiral stair cases				
	upto five level including curing but excluding the cost				
	of centring, shuttering, finishing and reinforcement				
	with. 1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20 mm nominal size)	0	e	e	-
33	Reinforcement for RCC work including	Kg	4665.37	87.18	406703.73
33	straightening, cutting ,bending ,binding and		0		0
	placing in position complete T.M.T Bars	l	X	250.00	2250 10
34	Centering and shuttering including strutting,	Sqm	12.78	262.30	3352.19
	propping etc. and removal of form work for:	e	0	0	2
	Foundations, footings, bases for columns		159.87	573.85	91741.40
35	Centering and shuttering including strutting,	sm	139.67	373.03	51711.10
	propping etc. and removal of form work for: Retaining walls, return walls, walls (any				
	Retaining walls, return walls, walls (any thickness) including attached pilasters				
	buttresses, plinth and string course fillets, kerbs				
	and steps etc.	e	Q .	e	-
36	Centering and shuttering including straightening	sm	16.95	502.85	8523.31
	propping etc. and removal of form work for:				
	Lintels, beams, plinth beams, girders, bressumers	0	0	0	0
	and cantilevers	2	101.00	625.60	6 4 9 9 9 4 6
37	Centering and shuttering including straightening	śm	101,99	635.60	64822.46
	propping etc, and removal of form work for:				
	Suspended floors, roofs, landings, balconies and	0	1	0	1
00	access platforms	y y	36,39	2086.80	75938.65
38	Centering and shuttering including strutting,	sqm	30.39	2000.00	13930.03
	propping etc. and removal of form for:Arches,	0	0	0	0
30	domes, vaults upto 6 m span 12mm Cement plaster of mix: 1 ; 4 (1 cement : 4	om .	66.72	286,05	19085.26
39	fine sand)	sm	00.74	200,00	0
40	12mm Cement plaster of mix; 1 : 3 (1 cement : 3 fine	Sm	66,35	378,12	25087.69
	TERM SCHICH DROUG OF HIAT I TO LI CERICII TO HIIC I	1111	CO.CO	OI OLLA	200000000000000000000000000000000000000

Head Draftsman

		Page No: 3	m			
		W S Scheme Harwan un	der Ju	Overtity	Allotted	Amount in Rs.
		Particulars of Items	Unit	Quantity	Rate	/ (110 and 111) (0
1			· L	1		20425.38
9		iding and mixing of water proofing	kg	352.77	57.90	20423.30
0	Prov	iding and mixing of water proofing	0	2	<u> </u>	8345.25
1	Cher	micals. Vide item no.5,6 & 7 @ 1kg/bag	Kg	62.61	133.30	6545.25
15.00	Contract vally make the					
						_
					0	
		i i i motinge traffies, guard but	R	l		355.95
	rail	ings, brackets, gates and similar works.	sqm	6.78	52.50	333.50
3				7	114.80	9640.90
	res	ra for shuttering in circular work (20 % of	sqm	83.98	114.00	
4	Ex	pective centring and shuttering remoj. tra for shuttering In circuilar work (20 % of chuttering items); Walls				
				0	2	1
	(ar	spective centring and shuttering received thickness) including attached pilasters, by thickness) including actuached pilasters,	e	N. S.	1008.45	36697.50
			sqm	36.39	1008.43	
45	C	entering and shuttering including straightening entering and shuttering including straightening form work for			0	\mathcal{Q}
	pr	entering and shuttering including out of form work for opping etc, and removal of form work for	D	e	100.60	1705.17
	D	omes v rigorilar work (20 % of	sqm	16.95	100.00	
46	E	omes xtra for shuttering In circuilar work (20 % of		0	1	l
	re	espective centring and situte in s	1		6802.12	195710.32
	,	lintels etc Brick work with common burnt clay F.P.S (non-	cum	28.77	0002.12	
47	E	Brick work with common burne stay nodular) bricks of class designation 75 in nodular) bricks of class designation 75 in nodular) bricks of class designation 75 in				
	r	modular) bricks of class deep mortar	1		l	l
	\ f	- and	L	25.32	1323.70	33518.68
			cum	23.32	1	
48	8	Extra for brick work in Super	1	50.42	650.00	32773.00
	-	plinth level upto floor V level. (by markets) Providing incorporating during Constt. Of P.G.I.	sqm	1 30.12		
4	9	sheet.	kgs	3390.0	102.13	346224.14
-	50		Rgo	3		
1 3	00	Structural steel work in built up constructing, without connecting plate including cutting,	100			0
1		n	1	1	L	85040.32
		hoisting, fixing in position and the coat of approved steel primer all complete.	sm	102.42	830.30	85040.32
+	51	coat of approved steel primer an compara- providing corrugated G.S sheet roofing including	r light,		March B.	
		Providing corrugated G.S sheet rooming were coated vertical/curved surface fixed with polymer coated vertical/curved surface fixed with polymer coated vertical/curved surface fixed with polymer coated vertical/curved surface fixed surface f				
		J or L hooks, bolts and fluts of with G.I				
		shope wherever reduited, 0.50iiiii diase	1	0		2
				21.50	626.70	13474.0
-	50		l m	r 21.50	020.70	
	52			4		
		hooks, bolts and nuts 80mm dia G.I limpet and	d	1 1	e	e
		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		1 24.30		Account to the same of the sam
-	E2	the state of the party of the p	of m	tr 34.38	500.00	
	53	200mm wide coloured including cost of holders	s,			
		angle supports complete job				

Head Draftsman

Technical Officer

Page No: 5th

Page No: 5th **W.S.Scheme Harwan under JJM**

	Particulars of Items	Unit	Quantity	Allotted	Amount in R
		1	e	Rate (
made o through end by shaft w inside operati fixing manuf streng	facture from high tensile steel wire of adequate of the confirming to IS 4454 part 1 and M.S top	sm	3.82	3238.20	12376.4
	of required thickness for rolling shutters. 25mm M.S laths with 1.25mm thick top cover	2	e .	l	L.
Provi	ding and fixing ball bearing for rolling	each	2.00	483.10	966.20
	iding wood work in frames of doors, windows,	cum	0.59	92065.35	54318.56
clere fram with (hol	estory windows and other frames, wrought ned and fixed in position with hold fast lugs or a dash fasteners of required dia and length ld fast lugs or with dash fasteners shall be d for separately): second class kail wood	Q	7	E	
7 Pro	oviding and fixing glazed shutters for doors,	sm	12.05	3338.05	40223.50
(4r ma of	ndows and clerestory windows using 10kg/sqm mm thick) float glass panes including ISI arked M.S pressed butt hinges bright finished required size with necessary screws. Second	l	0	0	0
	ass kail wood roviding & Laying in position reinforced cement	cum	4.21	10404.51	43802.99
p f	oncrete in arches, domes, vaults, shells, folded plate and roofs having slope more than 150 upto loor v excluding the cost of centring, shuttering, finishing and reinforcement with 1:2:4 mix (1 Cement : 2 Sand : 4 Graded stone aggregates) 20mm nominal size.	l	1	2	Į.
59	Cement concrete flooring 1:2:4 (1cement: 2 coarse sand: 4 graded stone aggregate) finished with a floating coat of neat cement including cement slurry and curing complete, but excluding the cost of nosing of steps etc. complete.50 mm thick	sm	46.41	555.50	25780.76
60	with 20mm nominal size stone aggregate. Providing and fixing panelled or panelled & glazed shutters for door windows using 4mm thick glass panes including MS pressed butt hinges bright finished off required size with necessary screws excl c/o glass panes		10.82	2784.10	30123.96
61	Providing and fixing panelling or panelling and glazing in panelled or panelled and glazed shutters for doors, windows and clerestory windows (Area of opening for panel inserts excluding portion inside grooves or rebates to be measured). Panelling for panelled or panelled and glazed shutters 25 mm to 40mm thick.		9.00	2501.75	22515.75
	digged chilitere 25 mm to 40mm thick				

Head Draftsman

Providing and fixing water closet squatting pan (Indian type W.C pan) with 100mm sand cast iron P or S trap, 10 litre low level PVC flushing cistern including flush pipe (of approved make) with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures compette including at the walls and floors wherever required. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests. Froviding and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap and making to the foot of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap and making to the walls etc. The providing and fixing of providing and making of U.3 mix (20mm nominal size). For Providing and fixing of soap dish of standard quality. Froviding and fixing of soap dish of standard quality. Froviding and fixing of soap dish of standard quality. Froviding and fixing of soap dish of standard quality. Froviding and fixing of soap dish of standard quality. Froviding and fixing Ismm G.I. pipes complete with G.I. fittings and clamps, including cutting and making good the walls etc. Froviding and fixing Ism G.I. pipes complete with G.I. fittings and clamps, including cutting and making good the walls etc. Froviding and fixing Ist quality ceramic glazed with G.I. fittings and clamps, including cutting and making good the walls etc. Froviding and fixing Ist quality ceramic glazed with G.I. fittings and clamps, including cutting and fixing Ist quality great of the provided provided the will etc. Froviding and fixing Ist quality ceramic glazed with gre		W.S.Scheme Harwan un	der JJI	M		
Providing and fixing water closet squatting pan [Indian type W.C pan] with 100mm sand cast iron P or S trap, 10 litre low level PVC flushing cistern including flush pipe [of approved make] with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures compelte including cutting and making good the walls and floors wherever required. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap 15mm C.P broviding and fixing 15mm C.P brass pillar tap 15mm C.P broviding and fixing 15mm C.P brass pillar tap 15mm C.P broviding and fixing 15mm C.P brass pillar tap 15mm C.P broviding and fixing 15mm C.P brass pillar tap 15mm C.P broviding and fixing 15mm C.P brass pillar tap 15mm C.P broviding and fixing 15mm C.P brass pillar tap 15mm C.P broviding and fixing 15mm C.P brass pillar tap 15mm C.P broviding and fixing 15mm C.P brass pillar tap 15mm C.P broviding and fixing 15mm C.P brass pillar tap 15mm		W.S.Scheme 22	Unit	Quantity	Allotted	Amount in Rs.
Providing and fixing water closet squatting pan (Indian type W.C pan) with 100mm sand cast in providing flush pipe (of approved make) with manually controlled device (handle lever) conforming to 1S: 7231, with all fittings and fixtures compelte including and making good the walls and floors wherever required. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot resis. 4 Providing and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x30mm with single 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x30mm with single 15mm C.P brass pillar taps 32mm C.P brass pillar taps 15mm C.P browling and fixing of soap dish of standard quality C.P providing and fixing 15mm G.I. pipes complete with C.I. fittings and clamps, including cutting and making good the walls etc providing & fixing on Terrace (at all floor levels) polyctheline water storage tank ISI 12701 marked indicating the Bis license no. with cover and suitable locking arrangement and making necessary holes for inlet, outlet and over flow pipes but without fittings and the base support for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. 71 Providing and fixing is made taps proved by Engineer: in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 ce		Particulars of items	0	2	Rate 👤	
Providing and fixing water closes squares Providing and post Provi	5.	Wing 200	Each	1.00	5534.80	5534.80
Indiant type W. C pan) with 100mlis and custors	Provio	ding and fixing water closet squatting pan	Daoi	A		
p or S trap, 10 litter low level PVC instances with including flush pipe (of approved make) with manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures competie including cutting and making good the walls and floors wherever required. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests. 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required. White Vitreous China of walls wherever required: White Vitreous China Plat back wash basin size 450x300mm with single 15mm C.P brass pillar taps 18 lack wash basin size 450x300mm with single 15mm C.P brass pillar tap incl. fixing to frame with 10mm dia bolts, nuts and wooden plugs and embedings in cement concreate block 30x10x15 cm (1:3) mix (20mm nominal size) 65 Providing and fixing of Furap PVC Class B 100 dia Providing and fixing of soap dish of standard quality 66 Providing and fixing of soap dish of standard quality 67 Providing and fixing 15mm G.I. pipes complete with G.I. fittings and clamps, including cutting and making good the walls set: 69 Providing & fixing on Terrace (at all floor levels) polyctheline water storage tank ISI 12701 marked indicating the BIS license no. with cover and suitable locking arrangement and making and making vall all license. 70 Providing & fixing on Terrace (at all floor levels) polyctheline water storage tank ISI 12701 marked indicating the BIS license no. with cover and suitable locking arrangement and making and making vall all license. 71 Providing and fixing 15m (charge) in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement :3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even	h.)	W C non with Hilling Sand Case	11/4			
including flush pipe (of approved manually controlled device (handle lever) conforming to IS: 7231, with all fittings and fixtures compelte including cutting and making good the walls and floors wherever required. White vitreous china orrisa pattern W.C Pan of Size 580x440 mm with intergal type foot rests waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap size of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap incl. fixing to frame with 10mm dia bolts, nuts and wooden plugs and embeddings in cement concreate block 30x10x15 cm (1:3) mix (20mm nominal size) 65 Providing and fixing of soap dish of standard quality 77 Providing and fixing of soap dish of standard quality 8 Pff of Pve pipes , vent etc with pv bends , traps etc complete job as per the requirement at site etc complete job as per the requirement at site with G.I. fittings and clamps, including and making good the walls etc with G.I. fittings and clamps, including and making good the walls etc with G.I. fittings and clamps, including and making good the walls etc with G.I. fittings and the base support for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. 70 Providing and fixing 15 guality ceramic glazed wall tiles conforming to 1S: 15022 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement :3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Pai		- 10 litro low level PVU llugining of				
manually conforming to IS: 7231, with all fittings and fixtures compelte including cutting and making good the walls and floors wherever required. White vitreous china orrisa pattern W.C. Pan of size 580x440 mm with intergal type foot rests size 580x440 mm with intergal type foot rests listed. Providing and fixing wash basin C.I brackets, I5mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap Providing 40x5mm flat iron hold fasts 40cm long incl. fixing to frame with 10mm dia bolts, nuts and wooden plugs and embedings in cement concreate block 30x10x15 cm (1:3) mix (20mm nominal size) 65 Providing and fixing of roap PVC Class B 100 dia common to a size of the complete job as per the requirement at site etc complete job as per the requirement at site etc complete job as per the requirement at site etc complete job as per the requirement at site etc omplete job as per the requirement at site etc omplete job as per the requirement at site providing and fixing 15mm G.I. pipes complete with G.I. fittings and clamps, including cutting and making good the walls etc. 70 Providing & Bis license no. with cover and suitable locking arrangement and making necessary holes for inlet, outlet and over flow pipes but without fittings and the base support for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. 71 Providing and fixing 15t quality ceramic glazed wall tiles conforming to 1S: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cment 13 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shad	inclu	ding flush pipe (of approved make)				
conforming to IS: 7231, with all littings and fixtures compette including cutting and making good the walls and floors wherever required. White vitreous china orrisa pattern W.C Pan of size 580x440 mm with intergal type foot rests Froviding and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap since 15mm C.P browling and fixing of soap dish of standard concreate block 30x10x15 cm (1:3) mix (20mm concreate complex concreate storage taps (1:3) mix (20mm concreate c						
fixtures compette including butting and good the walls and floors wherever required. White vitreous china orrisa pattern W.C. Pan of size 580x440 mm with intergal type foot rests is zize 580x440 mm with intergal type foot rests is zize 580x440 mm with intergal type foot rests is zize 580x440 mm with intergal type foot rests is zize 580x440 mm with including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap 65 Providing 40x5mm flat iron hold fasts 40cm long incl. fixing to frame with 10mm dia bolts, nuts and wooden plugs and embedings in cement concreate block 30x10x15 cm (1:3) mix (20mm nominal size) 66 Providing and fixing of soap dish of standard quality 77 Providing and fixing of soap dish of standard quality 88 P/f of Pve pipes , vent etc with pv bends , traps etc complete job as per the requirement at site with G.I. fittings and clamps, including cutting and making good the walls etc 70 Providing & fixing on Terrace (at all floor levels) polyetheline water storage tank ISI 12701 marked indicating the BIS license no. with cover and suitable locking arrangement and making necessary holes for inlet, outlet and over flow pipes but without fittings and the base support for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. 71 Providing and fixing Ist quality ceramic glazed wall titles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even between the provious content of the provider of the provider of the provider of t	The state of the s	10 . //31 \\//1111 \//1111 \\//111				
good the walls and lloof's White vitreous china orrisa pattern W.C Pan of Size \$80x440 mm with intergal type foot rests. 64 Providing and fixing wash basin C.I brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap 65 Providing 40x5mm flat iron hold fasts 40cm long incl. fixing to frame with 10mm dia botts, nuts and wooden plugs and embedings in cement concreate block 30x10x15 cm (1:3) mix (20mm nominal size) 66 Providing and fixing of P trap PVC Class B 100 dia 67 Providing and fixing of soap dish of standard quality 68 Pff of Pve pipes, vent etc with pv bends, traps etc complete job as per the requirement at site etc complete job as per the requirement at site with G.I. fittings and clamps, including cutting and making good the walls etc 69 Providing and fixing of Terrace (at all floor levels) provide the line water storage tank ISI 12701 marked possible to wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer, of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement :3 coarse sand) and jointing with grey cement sturry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 70 Providing and manufacturer to give an even weath through the provided and manufacture to give an even were casted to give an eve						
White vitreous china of riss pattern wisz 580x440 mm with intergal type foot rests size 580x440 mm with intergal type foot rests 15mm C.P brass pillar taps 32mm C.I brackets, 15mm C.P brass gillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap 65 Providing 40x5mm flat iron hold fasts 40cm long incl. fixing to frame with 10mm dia bolts, nuts and wooden plugs and embedings in cement concreate block 30x10x15 cm (1:3) mix (20mm nominal size) 66 Providing and fixing of soap dish of standard quality 77 Providing and fixing of soap dish of standard example of the complete job as per the requirement at site example of the with G.I. fittings and clamps, including cutting and making good the walls etc 70 Providing & fixing on Terrace (at all floor levels) polyetheline water storage tank ISI 12701 marked indicating the BIS license no. with cover and suitable locking arrangement and making necessary holes for inlet, outlet and over flow pipes but without fittings and the base support for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. 71 Providing and fixing ISI quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skiring, risers of steps and dados. over 12 mm thick bed of cement mortar 1:3 (1 cement 3 coarse sand) and jointing with grey cement slurry @ .3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even visited. The or more coals on new work.					0	0
size 580x440 mm with liftle gar type C.I. brackets, 15mm C.P brass pillar taps 32mm C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap 65 Providing 40x5mm flat iron hold fasts 40cm long incl. fixing to frame with 10mm dia bolts, nuts and wooden plugs and embedings in cement concreate block 30x10x15 cm (1:3) mix (20mm nominal size) 66 Providing and fixing of prap PVC Class B 100 dia 67 Providing and fixing of soap dish of standard quality et complete job as per the requirement at site etc complete job as per the requirement at site etc complete job as per the requirement at site with G.I. fittings and clamps, including cutting and making good the walls ctc 70 Providing & fixing on Terrace (at all floor levels) polyetheline water storage tank ISI 12701 marked indicating the BIS license no. with cover and suitable locking arrangement and making shotle green, black of any size as approved make, in all colours, shades except burgundy, bottle green, black of any size as approved make, in all colours, shades except burgundy, bottle green, black of any size as approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement :3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even bested Twee range casts on new work		china Orrisa Dalletti W.	Q	\mathcal{L}		7720.40
Providing and fixing wash oasin C.P brass waste of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap Providing 40x5mm flat iron hold fasts 40cm long incl. fixing to frame with 10mm dia bolts, nuts and wooden plugs and embedings in cement concreate block 30x10x15 cm (1:3) mix (20mm nominal size) Each Providing and fixing of P trap PVC Class B 100 dia Each Providing and fixing of soap dish of standard quality Providing and fixing of soap dish of standard quality Providing and fixing of soap dish of standard quality Providing and fixing and clamps, including cutting and making good the walls etc Providing & fixing on Terrace (at all floor levels) polyetheline water storage tank ISI 12701 marked indicating the BIS license no. with cover and suitable locking arrangement and making necessary holes for inlet, outlet and over flow pipes but without fittings and the base support for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement :3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. Provider Row or more ceals so no key work Provider Row or more ceals so no key work Provider Row or more ceals no new work Provider Row o			Fach	2.00	2769.20	5538.40
### 15mm C.P brass pillar teaps of standard pattern, including painting of fittings and brackets cutting and making the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap ### 15mm C.P brass pillar tap			Bacii			
waste of standard pattern, including the good of walls wherever required: White Vitreous China Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap 65 Providing 40x5mm flat iron hold fasts 40cm long incl. fixing to frame with 10mm dia bolts, nuts and wooden plugs and embedings in cement concreate block 30x10x15 cm (1:3) mix (20mm nominal size) 66 Providing and fixing of P trap PVC Class B 100 dia 67 Providing and fixing of soap dish of standard quality 68 Pff of Pvc pipes , vent etc with pv bends , traps etc complete job as per the requirement at site 69 Providing and fixing 15mm G.I. pipes complete with G.I. fittings and clamps, including cutting and making good the walls etc 70 Providing & fixing on Terrace (at all floor levels) polyetheline water storage tank ISI 12701 marked indicating the BIS license no. with cover and isuitable locking arrangement and making necessary holes for inlet, outlet and over flow pipes but without fittings and the base support for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. 71 Providing and fixing 15 tquality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slury @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even shaded. Two more cargon new work work	150	nm C.P brass pillar taps 32mm C.P brass				
fittings and brackets cutting and valls wherever required: White Vitreous China of walls wherever required: White Vitreous China Plat back wash basin size 450x300mm with single 15mm C.P brass pillar tap 65 Providing 40x5mm flat iron hold fasts 40cm long incl. fixing to frame with 10mm dia bolts, nuts and wooden plugs and embedings in cement concreate block 30x10x15 cm (1:3) mix (20mm nominal size) 66 Providing and fixing of Ptrap PVC Class B 100 dia 67 Providing and fixing of soap dish of standard quality 8 P/f of Pvc pipes, vent etc with pv bends, traps etc complete job as per the requirement at site etc complete job as per the requirement at site etc complete job as per the requirement at site with G.I. fittings and clamps, including cutting and making good the walls etc 70 Providing & fixing of Terrace (at all floor levels) polyetheline water storage tank ISI 12701 marked indicating the BIS license no. with cover and suitable locking arrangement and making necessary holes for inlet, outlet and over flow pipes but without fittings and the base support for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. 71 Providing and fixing Ist quality ceramic glazed will tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer: in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement :3 coarse sand) and jointing with grey cement slury @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even brand and manufacture to give an even						
of walls wherever required. Flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap flat back wash basin size 450x300mm with single 15mm C.P brass pillar tap flat back wash basin size 450x300mm with single 15mm C.P browiding and fixing of property of the providing and fixing of providing size as per the requirement at site flat back wash basin size 450x300mm with single 15mm C.P browiding and fixing of providing size as per the requirement at site flat back wash basin size 450x300mm with single 15mm C.P browiding and fixing of providing size as per the requirement at site flat back wash basin size as 40cm long inches in the size of the providing and fixing of providing and fixing of providing and fixing providing size as approved by be specified by the manufacturer, of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement :3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. flat back wash basin size as approved brand and manufacture to give an even size as even before an even work of the providing and the back work of the providing and the back of the prov	fitt	ings and brackets cutting and making the good				
single 15mm C.P brass pillar tap Flat back wash basin size 40cm long single 15mm C.P brass pillar tap Froviding 40x5mm flat iron hold fasts 40cm long incl. fixing to frame with 10mm dia bolts, nuts and wooden plugs and embedings in cement concreate block 30x10x15 cm (1:3) mix (20mm nominal size) 66 Providing and fixing of P trap PVC Class B 100 dia 67 Providing and fixing of soap dish of standard quality 68 P/f of Pvc pipes , vent etc with pv bends , traps etc complete job as per the requirement at site etc complete job as per the requirement at site with G.I. fittings and clamps, including cutting and making good the walls etc 70 Providing & fixing on Terrace (at all floor levels) polyetheline water storage tank ISI 12701 marked indicating the BIS license no. with cover and suitable locking arrangement and making necessary holes for inlet, outlet and over flow pipes but without fittings and the base support for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. 71 Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer: in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even	of	walls wherever required: White Vitreous China				
single 15mm C.P brease plinter of hold fasts 40cm long incl. fixing to frame with 10mm dia bolts, nuts and wooden plugs and embedings in cement concreate block 30x10x15 cm (1:3) mix (20mm nominal size) 66 Providing and fixing of prap PVC Class B 100 dia 67 Providing and fixing of soap dish of standard quality 88 Pff of Pvc pipes , vent etc with pv bends , traps etc complete job as per the requirement at site etc complete job as per the requirement at site with G.I. fittings and clamps, including cutting and making good the walls etc and making good the walls etc indicating the BIS license no. with cover and suitable locking arrangement and making necessary holes for inlet, outlet and over flow pipes but without fittings and the base support for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. 71 Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer: in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement .3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even	1776	st back wash basin size 4500000	0	2	L.	0721 20
Providing 40x5mm liat Iron liout abolts, nuts and wooden plugs and embedings in cement concreate block 30x10x15 cm (1:3) mix (20mm nominal size) Each 1.00 250.00 250.00	sir	ngle 15mm C.P brass pillar tap	Each	24.00	113.80	2/31.20
incl. fixing to frame with roth word and wooden plugs and embedings in cement concreate block 30x10x15 cm (1:3) mix (20mm nominal size) 66 Providing and fixing of P trap PVC Class B 100 dia 67 Providing and fixing of soap dish of standard quality 68 P/f of Pvc pipes, vent etc with pv bends, traps etc complete job as per the requirement at site etc omplete job as per the requirement at site with G.I. fittings and clamps, including cutting and making good the walls etc 70 Providing & fixing on Terrace (at all floor levels) polyetheline water storage tank ISI 12701 marked polyetheline water storage tank ISI 12701 marked indicating the BIS license no. with cover and suitable locking arrangement and making necessary holes for inlet, outlet and over flow pipes but without fittings and the base support for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. 71 Providing and fixing 1st quality ceramic glazed wall ties conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement :3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even work			Datoi:	419		
and wooden plugs and enhotenting concreate block 30x10x15 cm (1:3) mix (20mm nominal size) 66 Providing and fixing of P trap PVC Class B 100 dia 67 Providing and fixing of soap dish of standard quality 68 P/f of Pvc pipes , vent etc with pv bends , traps 69 Providing and fixing 15mm G.I. pipes complete etc complete job as per the requirement at site etc complete job as per the requirement at site with G.I. fittings and clamps, including cutting and making good the walls etc 70 Providing & fixing on Terrace (at all floor levels) reposite indicating the BIS license no. with cover and suitable locking arrangement and making necessary holes for inlet, outlet and over flow pipes but without fittings and the base support for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. 71 Providing and fixing ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement :3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even shad. The providing and manufacture to give an even shad. The providing and manufacture to give an even shad. The providing and manufacture to give an even shad. The providing and manufacture to give an even shad. The providing and manufacture to give an even shad. The provided provided the provided	in	cl. fixing to frame with 10mm dia bolts, nuts				1
concreate block 30x10x10 cm (cm) nominal size) 66 Providing and fixing of P trap PVC Class B 100 dia 67 Providing and fixing of soap dish of standard quality 68 P/f of Pvc pipes , vent etc with pv bends , traps etc complete job as per the requirement at site etc complete job as per the requirement at site with G.I. fittings and clamps, including cutting and making good the walls etc and making good the walls etc ployetheline water storage tank ISI 12701 marked polyetheline water storage tank ISI 12701 marked polyetheline water storage tank ISI 12701 marked indicating the BIS license no. with cover and suitable locking arrangement and making necessary holes for inlet, outlet and over flow pipes but without fittings and the base support for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. 71 Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement :3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even shed. The providing and give an even work				0	A Marie Park	
nominal size) 66 Providing and fixing of P trap PVC Class B 100 dia 67 Providing and fixing of soap dish of standard quality 88 P/f of Pvc pipes , vent etc with pv bends , traps etc complete job as per the requirement at site etc complete job as per the requirement at site etc complete job as per the requirement at site etc complete job as per the requirement at site etc complete job as per the requirement at site etc complete job as per the requirement at site etc complete job as per the requirement at site etc complete job as per the requirement at site etc complete job as per the requirement at site etc complete job as per the requirement at site etc complete job as per the requirement at site etc complete job as per the requirement at site etc complete job as per the requirement at site etc complete job as per the requirement at site etc complete job as per the requirement at site etc complete. The providing and fixing 15 mm d.l. pipes complete job as per the requirement at site etc complete. The providing and fixing 15 mm d.l. pipes complete job as per the requirement at site etc complete. The providing and fixing sind clamps, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even shede Two or more coats on new work and complete.	C	oncreate block 30x10x15 cm (1:3) IIIX (201111)	e	> <u>L</u>	70.00	250.00
67 Providing and fixing of soap dish of standard quality 68 P/f of Pvc pipes , vent etc with pv bends , traps etc complete job as per the requirement at site 69 Providing and fixing 15mm G.I. pipes complete with G.I. fittings and clamps, including cutting and making good the walls etc 70 Providing & fixing on Terrace (at all floor levels) polyetheline water storage tank ISI 12701 marked indicating the BIS license no. with cover and suitable locking arrangement and making necessary holes for inlet, outlet and over flow pipes but without fittings and the base support for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. 71 Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even elected. The provided is a provided and manufacture to give an even elected. The providing and manufacture to give an even elected.			Each	1.00	250.00	1
67 Providing and fixing of soap dish of standard quality 68 P/f of Pvc pipes, vent etc with pv bends, traps etc complete job as per the requirement at site 69 Providing and fixing 15mm G.I. pipes complete with G.I. fittings and clamps,including cutting and making good the walls etc 70 Providing & fixing on Terrace (at all floor levels) polyetheline water storage tank ISI 12701 marked indicating the BIS license no. with cover and suitable locking arrangement and making necessary holes for inlet, outlet and over flow pipes but without fittings and the base support for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. 71 Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even ended Type or more coats on new work	66 P	roviding and fixing of P trap PVC Class B 100 day	Fach	1.00	285.00	285.00
68 Pf of Pvc pipes , vent etc with pv bends , traps etc complete job as per the requirement at site etc complete job as per the requirement at site etc complete job as per the requirement at site etc complete job as per the requirement at site etc complete with G.I. fittings and clamps,including cutting and making good the walls etc and making good the walls etc polyetheline water storage tank ISI 12701 marked indicating the BIS license no. with cover and suitable locking arrangement and making necessary holes for inlet, outlet and over flow pipes but without fittings and the base support for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. 71 Providing and fixing lst quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement :3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even shed Two or more coats on new work	C7 I	Providing and fixing of soap dish of standard	Each	1.00		12222 00
etc complete job as per dir teregram G.I. pipes complete with G.I. fittings and clamps, including cutting and making good the walls etc 70 Providing & fixing on Terrace (at all floor levels) polyetheline water storage tank ISI 12701 marked indicating the BIS license no. with cover and suitable locking arrangement and making necessary holes for inlet, outlet and over flow pipes but without fittings and the base support for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. 71 Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement :3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade Twe or more coats on new work	0/ 1	quality trops	ioh /	2.00	6000.00	12000.00
etc complete job as per dir teregram G.I. pipes complete with G.I. fittings and clamps, including cutting and making good the walls etc 70 Providing & fixing on Terrace (at all floor levels) polyetheline water storage tank ISI 12701 marked indicating the BIS license no. with cover and suitable locking arrangement and making necessary holes for inlet, outlet and over flow pipes but without fittings and the base support for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. 71 Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement :3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade Twe or more coats on new work	68	P/f of Pvc pipes, vent etc with pv bends, traps	1000	0	and the second	16592.08
with G.I. fittings and clamps, including cutting and making good the walls etc 70 Providing & fixing on Terrace (at all floor levels) polyetheline water storage tank ISI 12701 marked indicating the BIS license no. with cover and suitable locking arrangement and making necessary holes for inlet, outlet and over flow pipes but without fittings and the base support for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. 71 Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even sheds Two or more coats on new work	00	etc complete job as per the requirement at site	m	55.20	300.40	10502.00
with G.I. fittings and claimps, metalog and making good the walls etc 70 Providing & fixing on Terrace (at all floor levels) polyetheline water storage tank ISI 12701 marked indicating the BIS license no. with cover and suitable locking arrangement and making necessary holes for inlet, outlet and over flow pipes but without fittings and the base support for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. 71 Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement :3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even sheds? Two or more coats on new work	69	Providing and fixing 15mm G.I. pipes complete				1
and making good in Refrace (at all floor levels) Providing & fixing on Terrace (at all floor levels) polyetheline water storage tank ISI 12701 marked indicating the BIS license no. with cover and suitable locking arrangement and making necessary holes for inlet, outlet and over flow pipes but without fittings and the base support for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. 71 Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement:3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even shede Two er more coats on new work		with G.I. fittings and clamps, mercans		2	12.00	13000.00
polyetheline water storage tank to cover and indicating the BIS license no. with cover and suitable locking arrangement and making necessary holes for inlet, outlet and over flow pipes but without fittings and the base support for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. 71 Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even shede Two or more coals on new work		and making good the walls etc			13.00	10000
indicating the BIS license flow suitable locking arrangement and making necessary holes for inlet, outlet and over flow pipes but without fittings and the base support for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. 71 Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement:3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade Two or more coats on new work	70	Providing & fixing off Terrace (and ISI 12701 marked		0		
suitable locking arrangement and over flow necessary holes for inlet, outlet and over flow pipes but without fittings and the base support for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. 71 Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement :3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even speed Two or more coats on new work		polyetheline water storage that he polyetheline water storage to with cover and				
necessary holes for lifter, other than pipes but without fittings and the base support for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. 71 Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade. Two or more coats on new work		indicating the bio horangement and making			1 1 1 1 1 1 1	
pipes but without fittings and the Star, Lotus or for tank (sintex, Electroplast, Star, Lotus or equivalent having valid ISI license. 71 Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement:3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even elseda Two or more coats on new work						
for tank (sintex, Electropiast, odar, equivalent having valid ISI license. 71 Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement:3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even speeds. Two or more coats on new work.						0
Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even chade Two or more coats on new work		for tonk (sintex. Electroplast, Star,	0	0	1	
Providing and fixing 1st quality tertainly great wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement:3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade Two or more coats on new work				16.99	1161.05	19726.24
wall tiles conforming to 15. 13022 (the specified by the manufacturer), of approved be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement :3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade Two or more coats on new work	71	1 France let dilativ Culture Brown				
make, in all colours, shades except stages by bottle green, black of any size as approved by Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement :3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even check Two or more coats on new work						
bottle green, black of any size as approved Engineer- in-Charge, in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1:3 (1 cement :3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even checker. 73 Painting with synthetic enamel paint of approved brand and manufacture to give an even checker.		be specified by the manufacturer, of deprivation of the specified by the manufacturer, of the specified by the	,			
Engineer- in-Charge, in skilting, fisched of cement and dados over 12 mm thick bed of cement mortar 1:3 (1 cement :3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even charge of the da Two or more coats on new work						
and dados over 12 mm thick sed of mortar 1:3 (1 cement :3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade Two or more coats on new work				- I de la companya d		
mortar 1:3 (1 cement :3 coarse said) and joining with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even check Two or more coats on new work						
with grey cement sturry (a) 3.3 kg pet square, including pointing in white cement mixed with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even sphered Two or more coats on new work		1 0 (1 coment '3 coarse sally and joint of				
including pointing in white centerit linked with pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even check Two or more coats on new work						1
pigment of matching shade complete. 72 Painting with synthetic enamel paint of approved brand and manufacture to give an even check Two or more coats on new work		including pointing in white cellent mixed with	h ()	1		2
Painting with synthetic enamel paint of approved brand and manufacture to give an even brand Two or more coats on new work		af matching shade complete.		10 17	121 95	1520.72
brand and manufacture to give an even	72	Deinting with synthetic enamel paint of approve	a sm	12,47	121.50	
shade Two or more coats on new Work		brand and manufacture to give all eve	n			
		shade.Two or more coats on new work	and a resident of the state of	the principal little and advantage of the little and the little an		P

Head Draftsman

Technical Officer

Page No: 7th



W.S.Scheme Harwan under JJM

S.	Particulars of Items	Unit	Quantity	Allotted Rate	Amount in Rs.
NO NO		l	1.000		23967.24
73	Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade on New work (two or more coats) over	sm	160.80	149.05	23907.24
	and including priming coat with water thinnable	8	2	e.	1
74	Providing and fixing aluminum handles ISI marked anodized (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed	Each	10.00	52.30	523.00
	to required colour and shade with necessary screws etc. complete. 100mm	Q	J.		1147.00
75	Providing and fixing aluminum tower bolts ISI marked anodized (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed	Each	20.00	57.35	1147.00
	to required colour or shade with necessary screws	l	R	J	710000
76	etc. complete: 100mm Providing anf Fixing Sliding door bolts heavy duty	Each	3.00	1800.00	5400.00 1309.50
77	Providing and fixing 15 mm nominal bore C.P.	Each	3.00	436.50 💋	
78	brass bib cock of app Quality Electrification of pump House by providing fixing/fittings of switches, boxes, Boards, MCB	Job	1.00	6000.00	6000.00
	etc. of standard qualities ISI mark etc (complete	d	3.00	2000.00	6000.00
79	t I I area by providing	Poin t	2	l	10500.00
80	Electrification of pump House by providing fixing/fittings of Lightening points incld. all	Poin t	7.00 L	1500.00	1
8	accessories 1 Providing and fitting of service line 7/16 of	m	30.00	150.00	4500.00
8	specified specification complete job Carriage of pipes by Mechanical transport from source to actual site of work including loading, unloading and stacking of material: pipes for avg lead of 15km	MT (50.17	303.64	15232.52
8	Carriage of materials by Mechanical transport from source to actual site of work including loading, unloading and stacking of material: 20mm stone aggregate for avg lead 25 km	cum	60.14	451.97 _	27181.48
8	4 Carriage of materials by Mechanical transport from source to actual site of work including loading, unloading and stacking of material: 40mm stone aggregate for avg. lead 20km		10.88	437.29	4757.72
8	5 Carriage of materials by Mechanical transport from source to actual site of work including loading, unloading and stacking of material: Sand	cum	46.09	451.97	20831.30
8	for avg lead 25 km Carriage of materials by Mechanical transport from source to actual site of work including loading, unloading and stacking of material: Stone soilng for avg lead 10km		40.09	330,42	13246.46

Head Draftsman

W.S.Scheme Harwan under JJM

5.	Particulars of Items	Unit	Quantity 40.88	Allotted Rate &	Amount in Rs. 2 2 4 14618.67
	Carriage of materials by Mechanical transport from source to actual site of work including loading, unloading and stacking of material: Cement/Steel from from Divisional store for avg lead 20kms Carriage of materials by Mechanical transport from source to actual site of work including loading, unloading and stacking of material: bricks for avg 75km lead Head load from stone aggregate from dumping site upto actual site of work by avg. lead 300mtr	no Cum	13666.00 2 45.76 15.33	2.53 £ 515.75 £ 359.20	23600.72 5506.54
90	Head load from Centerty been lead 300mtr	8	6.10	515.75	3146.09
91	upto actual site of work by avg. lead of the dumping site lead load from stone soiling from dumping site upto actual site of work by avg. lead 300mtr				6395717.21
	Total Above 1.80% on all itmes				115122.90 6510840.00
	Allotted Cost		1		8310040.00

Rates and quantities checked:

Head Draughtsman

Officer Technical

Executi Jal Shakti PHE Division Sopore

Terms and conditions:

- 1. Total amount of the work should in no case exceed beyond Rs.6510840.00 (Rs.Sixty five lacs ten thousand eight hundred and forty only) which includes all taxes, levies etc.
- 2. The work shall have to be completed by you within a period of 90 days failing which the panality under rules shall be imposed upon you.
- 3. Performance security @ 3% of allotted cost i,e Rs.195325.00 in shape of CDR/BG/FDR shall have be deposited by you in this office within seven days from the date of issue of this allotment from this office failing which action shall be initiated as per SBD of the NIT.
- 4. An agreement shall have to be drawn by you with the department within a period of 07 days from the date of issuance of allotment, failure to executed such a formal deed shall not however prevent the contract from being enforced upon you. However payment on account of this work shall not be considered in absence of agreement.
- 5. The earnest money amounting to Rs.101180/= & Rs.26740/= deposited by you in this office as a bid security against the contract vide CDR No: 3156086 & No: 3396403 dated : 05-11-2022 & dated: 28-11-2022 respectively shall be considered for release once the performance security @ 3% of allotted amount is deposited by you.

Page No: 9th W.S.Scheme Harwan under JJM

- 6. The allotted work shall have to be monitored by Third Party Monitoring Agency (WAPCOAS) appointed by the department.
- 7. All other terms and conditions shall remain same as laid down in E-NIT/ Standard bidding document/PWD from No 25 and GFR-2017,

Assistant Accounts

Officer

Technical officer

Executive Engineer Jal Shakti PHE Division

Copy to the:

Chief Engineer Kashmir Jal Shakti PHE Department Srinagar for favour of information.

District Development Commissioner Baramulla (Chairperson DJJM) for favour of information.

Superintending Engineer Hydraulic Circle Baramulla/Bandipora (Member Secretary JJM) for favour of

iv) Assistant Executive Engineer PHE Sub Division Sopore for information and necessary action.

v) M/S WAPCOAS Ltd Corporate office 76-C intuitional area sector 18 Gurgon for information.

vi) File Concerned.